


1	ECOLINE® ADH single ply membrane single ply membrane fully bonded using adh adhesive
2	ADH adhesive
3	HYTHERM® tapered / flat board insulation fully bonded using Hyra-Stik adhesive (thickness to achieve design U-value and/or design fall)
4	Heat welded seam - 40mm
5	ECO/R cover strip
6	Mechanically fixed hard edge/batten (by specialist subcontractor)
7	ECOMETAL® preformed PVC coated metal trim mechanical (MTP) fixing at 200mm ctrs
8	Lead apron flashing (by specialist subcontractor)
9	ECOLINE® air & vapour control layer (AVCL)
10	Vernis Antac ST Primer
11	Plywood roof deck by specialist contractor
12	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)
13	Batten and tiles / slates (by specialist subcontractor)



Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOLINE® ADH TYPICAL MANSARD  
EDGE DRIP DETAIL

DWG.No  
WR.P.EL.adh.110

SCALE  
1:5 @ A4

DATE  
2019

REV (if applicable)

N/A

STANDARD DETAIL

EI

Ecoline