


|    |   |
|----|---|
| 1  | DPC/cavity tray/weep holes to drain internally or externally as specified   |
| 2  | ECOLINE® sealant  |
| 3  | ECOMETAL® preformed PVC coated metal trim mechanical (C) fixing at 200mm ctrs   |
| 4  | FM/D contact adhesive   |
| 5  | ECOLINE® FM single ply membrane   |
| 6  | ADH adhesive  |
| 7  | HYTHERM® tapered / flat board insulation fully bonded using Hyra-Stik adhesive (thickness to achieve design U-value and/or design fall) |
| 8  | ECOLINE® air & vapour control layer (AVCL)  |
| 9  | Restraint bar and mechanical (C) fixing   |
| 10 | Heat welded seam - 40mm   |
| 11 | ECOLINE® ADH fleeceback fully bonded using ADH adhesive   |
| 12 | Vernis antac ST primer  |
| 13 | Plywood roof deck by specialist contractor  |
| 14 | Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)   |



www.axterhd.co.uk  
info@axterhd.co.uk  
01473 724058
Axter Ltd  
West Road, Ransomes Europark,  
Ipswich, Suffolk, IP3 9BX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOLINE® ADH TYPICAL INSULATED SKIRTING UPSTAND TO BRICK PARAPET DETAIL

DWG.No  
**WR.P.EL.adh.20**

SCALE  
**1:5 @ A4**

DATE  
**2019**

REV (if applicable)  
**N/A**

STANDARD DETAIL

**EI**

Ecoline