

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : HYRANGER® TYPICAL MOVEMENT
JOINT - TWIN KERB DETAIL

DWG.No
WR.C.HY.140

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)

N/A

STANDARD DETAIL

Hy

Hyranger

- | | |
|----|---|
| 1 | HYRANGER® SPOT under-layer |
| 2 | HYRANGER® Capping Sheet |
| 3 | HYTHERM® ADH tapered/flat board |
| 3 | Insulation (thickness to achieve design U-value and/or design fall) |
| 4 | 35PY Angle Strip |
| 5 | 18mm WBP Plywood deck capping (fixed one side only) |
| 6 | Timber packers to top by others |
| 7 | Non-flammable compressible foam |
| 8 | AXTER® Bitumseal sealant to create air tight seal |
| 9 | HYRANGER® Detail Membrane |
| 10 | Timber batten (by specialist subcontractor) |
| 11 | HYRANGER® to form welted drip detail |
| 12 | Vernis Antac ST Primer |
| 13 | HYRANGER® air & vapour control layer (AVCL) |
| 14 | Concrete roof slab by specialist contractor |

