Cf

Cityflor

LEGEND:

1	Soft metal flashing by others
2	35PY angle reinforcement
3	500mm min. Fire break/ ballast sterile area (aggregate size 20-40mm) in accordance with GRO code of practice
4	Perforated retaining angle
5	CITYFLOR detail membrane
6	HYTHERM tapered/flat board insulation (thickness to achieve design U-value and/or minimum 1:40 design fall)
7	CITYFLOR primer
8	CITYFLOR air and vapour control layer (AVCL)
9	CITYFLOR underlayer
10	CITYFLOR capsheet
11	Concrete roof slab (minimum 1:80 finished fall) by specialist contractor
12	BIOSOLAR living roof system, drainage board and filtration layer (in accordance with GRO code of practice)
13	BIOSOLAR photovoltaic (PV) support profile by specialist contractor

DESIGN NOTE: This drawing is a guide only and should not be used for construction. Do not scale from this drawing. Axter accepts no liability whatsoever in the event this drawing is relied upon for construction.

DRAWING TITLE
TYPICAL PERIMETER DETAIL WITH BIOSOLAR SYSTEM

DWG TYPE : STANDARD DETAIL

DWG No. : CF.C.WR.pv.030

REV No. : N/A | **DRAWN BY :** NS

DATE : 11/2023 | **SCALE :** NTS

AXTER
www.axterltd.co.uk info@axterltd.co.uk