Waterproofing system section

Cf

Cityflor

LEGEND:

1	CITYFLOR top layer
2	CITYFLOR underlayer
3	HYTHERM tapered/flat board insulation (thickness to achieve design U-value and/or minimum 1:40 design fall)
4	CITYFLOR air and vapour control layer (AVCL)
5	CITYFLOR primer
6	Concrete roof slab (minimum 1:80 finished fall) by specialist contractor
7	BIOSOLAR living roof system, drainage board and filtration layer (in accordance with GRO code of practice)
8	BIOSOLAR photovoltaic (PV) support profile by specialist contractor

DIMENSIONS:

A	Solar panels should be positioned to allow sufficient space to allow for safe and practical maintenance of both the panels and the living roof

DESIGN NOTE: This drawing is a guide only and should not be used for construction. Do not scale from this drawing. Axter accepts no liability whatsoever in the event this drawing is relied upon for construction.

DRAWING TITLE
TYPICAL EAST-WEST BIOSOLAR DETAIL

DWG TYPE : STANDARD DETAIL

DWG No. : CF.C.WR.pv.020

REV No. : N/A | **DRAWN BY :** NS

DATE : 11/2023 | **SCALE :** NTS

AXTER
www.axterltd.co.uk info@axterltd.co.uk