

# Declaration of Performance

ALPAL 3000 S

<b>1.</b>	<b>Identification code</b>	ALPAL 3000 S
<b>2.</b>	<b>Intended use</b>	Reinforced bitumen sheets for roof waterproofing.
<b>3.</b>	<b>Manufacturer</b>	IKO-AXTER, 6 rue Laferriere, 75009 PARIS, France <a href="http://www.axter.co.uk/downloads">www.axter.co.uk/downloads</a>
<b>4.</b>	<b>Authorised representative</b>	N/A
<b>5.</b>	<b>System of assessment and verification of constancy of performance of the product</b>	System 2+
<b>6a.</b>	<b>Product covered by the harmonised standard</b>	EN 13707 The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
<b>6b.</b>	<b>European Technical Assessment</b>	N/A

## 7. Declared performance

Essential characteristics		Performance				Harmonised technical specification	
		Value	Tolerance		Units		
			Min	Max			
Resistance to tearing (nail shank)	Longitudinal	200	180	-	N	EN 13707:2014	
	Cross direction	250	230	-			
Tensile properties: maximum tensile force	Longitudinal	600	500	-	N/50mm		
	Cross direction	600	500	-			
Tensile properties: elongation	Longitudinal	35	25	-	%		
	Cross direction	35	25	-			
Peel resistance of joint	Maximum force	Selvedge	150	100	-		N/50mm
		End joint	150	100	-		
	Average force	Selvedge	NA	-	-		
		End joint	NA	-	-		
Shear resistance of joint	Maximum force	Selvedge	600	500	-		
		End joint	600	500	-		
Flexibility at low temperature		-15	≤		°C		
Durability EN 1296	Flow resistance at elevated temperature	120	110	-	°C		
Durability EN 1297	Visible defects	NA					
Resistance to impact		600	≥		mm		
Resistance to static loading (method A)		20	≥		kg		
Watertightness under 10 kPa		Conform			-		
Resistance to root penetration		NA			-		
Resistance to external fire exposure		FRoof (Note 1)			-		
Reaction to fire		NPD			-		
Dangerous substances		Note 2 and 3			-		

NA: Not applicable due to use of product.

NPD: No performance determined.

Note 1: As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performance of the product identified above is in conformity with the set of declared performance/s. In accordance with Regulation (EU) No 305/211, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

Only the most recent published version of this document is valid, available at [www.axter.co.uk/downloads](http://www.axter.co.uk/downloads). Once downloaded, documents are uncontrolled so users should always ensure they are referring to the latest version. Further assistance is available from Axter Ltd's Technical Support Team, email: [technical@axterltd.co.uk](mailto:technical@axterltd.co.uk).

Signed for and on behalf of the manufacturer by:  
Peter Fleischmann (Chairman)



Paris  
05/09/2024