

Declaration of Performance

ARMALU

1. Identification code	ARMALU
2. Intended use	Reinforced bitumen sheets for roof waterproofing. Bitumen water vapour control layers.
3. Manufacturer	IKO-AXTER, 6 rue Laferriere, 75009 PARIS, France www.axter.co.uk/downloads
4. Authorised representative	N/A
5. System of assessment and verification of constancy of performance of the product	System 2+ System 3
6a. Product covered by the harmonised standard	<p>EN 13707 The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.</p> <p>The SGS INTRON Certification B.V, notify body n° 0958 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0958-CPR-2016/3.</p> <p>EN 13970 Declaration of the performance of the essential characteristics by the manufacturer.</p>
6b. European Technical Assessment	N/A

7. Declared performance

Essential characteristics			Performance				Harmonised technical specification
			Value	Tolerance		Units	
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal	350	250	-	N	EN 13707:2014 EN 13970:2005/ A1:2007	
	Cross direction	350	250	-			
Tensile properties: maximum tensile force	Longitudinal	900	600	-	N/50mm		
	Cross direction	900	600	-			
Tensile properties: elongation	Longitudinal	5	3	-	%		
	Cross direction	5	3	-			
Reaction to fire			NPD		-		
Dangerous substances			Note 2 and 3		-		
Peel resistance of joint	Maximum force	Selvedge	NA	-	-		N/50mm
		End joint	NA	-	-		
	Average force	Selvedge	NA	-	-		
		End joint	NA	-	-		
Shear resistance of joint	Maximum force	Selvedge	NA	-	-		
		End joint	NA	-	-		
Flexibility at low temperature			-10	≥	°C	EN 13707:2014	
Resistance to impact (method A)			NA	≥	mm		
Durability EN 1296	Flow resistance at elevated temperature		100	85	-		°C
Durability EN 1297			Visible defects		NA		
Resistance to static loading (method A)			NA	≥	kg		
Resistance to root penetration			NA		-		
Resistance to external fire exposure			FRoof (Note 1)		-		
Watertightness under 10 kPa			Conform		-		
Watertightness under 2 kPa			Conform		-		
Water vapour transmission properties			≥1000		-		EN 13970:2005/ A1:2007
Durability EN 1296	Water vapour transmission		≥1000		m		
Durability EN 1847	Water vapour transmission		NPD		m		

NA: Not applicable due to use of product. NPD: No Performance Determined

Note 1: As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performance of the product identified above is in conformity with the set of declared performance/s. In accordance with Regulation (EU) No 305/211, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

Only the most recent published version of this document is valid, available at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled so users should always ensure they are referring to the latest version. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk.

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Chairman)



Paris
09/02/2024