

Declaration of Performance

FORCE LINE 4.5 RE GB

1.	Identification code	FORCE LINE 4.5 RE GB
2.	Intended use	Reinforced bitumen sheets for roof waterproofing.
3.	Manufacturer	IKO-AXTER, 6 rue Laferriere, 75009 PARIS, France www.axter.co.uk/downloads
4.	Authorised representative	N/A
5.	System of assessment and verification of constancy of performance of the product	System 2+
6a.	Product covered by the harmonised standard	EN 13707 The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
6b.	European Technical Assessment	N/A

7. Declared performance

Essential characteristics			Performance			Harmonised technical specification	
			Value	Tolerance			Units
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal	NA	-	-	N	EN 13707:2014	
	Cross direction	NA	-	-			
Tensile properties: maximum tensile force	Longitudinal	700	400	-	N/50mm		
	Cross direction	550	400	-			
Tensile properties: elongation	Longitudinal	40	30	-	%		
	Cross direction	50	40	-			
Peel resistance of joint	Maximum force	Selvedge	NA	-	-		N/50mm
		End joint	NA	-	-		
	Average force	Selvedge	NA	-	-		
		End joint	NA	-	-		
Shear resistance of joint	Maximum force	Selvedge	550	400	-		N/50mm
		End joint	700	400	-		
Flexibility at low temperature			-10	≤			°C
Durability EN 1296	Flow resistance at elevated temperature		100	90	-		°C
Durability EN 1297	Visible defects		NA				
Resistance to impact			600	≥			mm
Resistance to static loading (method A)			20	≥			kg
Watertightness under 10 kPa			Conform				-
Resistance to root penetration			NA				-
Resistance to external fire exposure			F _{Roof} (Note 1)				-
Reaction to fire			NPD			-	
Dangerous substances			Note 2 and 3			-	

NA: Not applicable due to use of product.

NPD: No performance determined.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performance of the product identified above is in conformity with the set of declared performance/s. In accordance with Regulation (EU) No 305/211, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

Only the most recent published version of this document is valid, available at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled so users should always ensure they are referring to the latest version. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk.

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Chairman)



Paris
09/02/2024