

Declaration of Performance

ROLLSTICK 31 ALPA ALU

| | |
|--|--|
| 1. Identification code | ROLLSTICK 31 ALPA ALU |
| 2. Intended use | Bitumen air and water vapour control layers. |
| 3. Manufacturer | IKO-AXTER, 6 rue Laferriere, 75009 PARIS, France www.axter.co.uk/downloads |
| 4. Authorised representative | N/A |
| 5. System of assessment and verification of constancy of performance of the product | System 3 |
| 6a. Product covered by the harmonised standard | EN 13707 Declaration of the performance of the essential characteristics by the manufacturer. |
| 6b. European Technical Assessment | N/A |

7. Declared performance

| Essential characteristics | | Performance | | | | Harmonised technical specification |
|---|---------------------------|--------------|-----------|-----|---------|------------------------------------|
| | | Value | Tolerance | | Units | |
| | | | Min | Max | | |
| Resistance to tearing (nail shank) | Longitudinal | 150 | 50 | - | N | EN 13970:2005/ A1:2007 |
| | Cross direction | 150 | 50 | - | | |
| Tensile properties: maximum tensile force | Longitudinal | 550 | 300 | - | N/50 mm | |
| | Cross direction | 350 | 250 | - | | |
| Tensile properties: elongation | Longitudinal | 15 | 5 | - | % | |
| | Cross direction | 40 | 15 | - | | |
| Resistance to impact | | NA | | | mm | |
| Watertightness under 2 kPa | | Conform | | | - | |
| Water vapour transmission properties | | 1000 | | | m | |
| Durability EN 1296 | Water vapour transmission | 1000 | | | m | |
| Durability EN 1847 | Water vapour transmission | NPD | | | m | |
| Reaction to fire | | NPD | | | - | |
| Dangerous substances | | Note 1 and 2 | | | - | |

NA: Not applicable due to use of product.

NPD: No performance determined.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performance of the product identified above is in conformity with the set of declared performance/s. In accordance with Regulation (EU) No 305/211, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

Only the most recent published version of this document is valid, available at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled so users should always ensure they are referring to the latest version. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk.

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Chairman)



Paris
09/02/2024