

# Declaration of Performance

VAP AL SK

<b>1. Identification code</b>	VAP AL SK
<b>2. Intended use</b>	Bitumen air and water vapour control layers
<b>3. Manufacturer</b>	IKO-AXTER 6, rue Laferrière 75009 Paris France <a href="http://www.axter.eu/dop">www.axter.eu/dop</a>
<b>4. Authorised representative</b>	N/A
<b>5. System of assessment and verification of constancy of performance of the product</b>	System 3
<b>6a. Product covered by the harmonised standard:</b>	EN 13970 Declaration of the performance of the essential characteristics by the manufacturer
<b>6b. European Technical Assessment:</b>	N/A

**7. Declared performance**

Essential characteristics			Performance				Harmonised technical specification
			Value	Tolerance		Units	
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal	150	50		N	EN 13970:2005/ A1:2007	
	Cross direction	150	50				
Tensile properties: maximum tensile force	Longitudinal	500	300		N/50mm		
	Cross direction	350	250				
Tensile properties: elongation	Longitudinal	15	5		%		
	Cross direction	40	15				
Shear resistance of joint	Maximum force	Selvedge	NPD	-	-		N/50mm
		End joint	NPD	-	-		
Resistance to impact			NPD				mm
Watertightness under 2 kPa			Conform				-
Water vapour transmission properties			≥1500				m
Durability EN 1296	Water vapour transmission		≥1500				m
Durability EN 1847	Water vapour transmission		NPD				m
Reaction to fire			NPD				-
Dangerous substances			Note 1 and 2			-	

NA: not applicable due to use of product. NPD: No Performance Determined.

Note 1 : This product does not contain asbestos or tar constituents.

Note 2 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performance of the product identified above is in conformity with the set of declared performance/s. In accordance with Regulation (EU) No 305/211, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

Only the most recent published version of this document is valid, available at [www.axter.co.uk/downloads](http://www.axter.co.uk/downloads). Once downloaded, documents are uncontrolled so users should always ensure they are referring to the latest version. Further assistance is available from Axter Ltd's Technical Support Team, email: [technical@axterltd.co.uk](mailto:technical@axterltd.co.uk).

Signed for and on behalf of the manufacturer by:  
Peter Fleischmann (Managing Director)



Paris  
09/02/2024