



6b.	European Technical Assessment:	N/A				
	harmonised standard:	Declaration of the performance of the essential characteristics by the manufacturer				
6a.	Product covered by the	EN 13970				
5.	System of assessment and verification of constancy of performance of the product	System 3				
4.	Authorised representative	N/A				
		www.axter.eu/dop				
3.	Manufacturer	AXTER SAS, 6 rue Laferrière, 75009 PARIS, France				
2.	Intended use	Bitumen air and water vapour control layers				
1.	Identification code	ROLL 25 ALPA ALU				

Declared performance

Essential characterist	Performance				Harmonised		
				Tolerance		Units	technical specification
				Min	Max		
Resistance to	Longitudinal		160	120	200	N	
tearing (nail shank)	Cross direction		150	110	200		
Tensile properties: maximum tensile	Longitudinal		500	300	700	N/50 mm	
force	Cross direction		350	250	450		
Tensile properties:	Longitudinal		15	5	35	%	
elongation	Cross direction		40	15	50	%	
Shear resistance	Maximum force	Selvedge	NPD	-	-	N/50mm	EN 13970:2005/
of joint	IVIAXIMUM TORCE	End joint	NPD	-	-		
Flexibility at low temp	NA	≤		°C	A1:2007		
Resistance to impact	500	mm		mm			
Watertightness under	NA			-			
Water vapour transmi	1000	m		m			
Durability EN 1296 Water vapour transmission			1100	m		m	
Durability EN 1847 Water vapour transmission			NPD			m	
Reaction to fire	NPD			-			
Dangerous substance	Note 1 and 2			-			

 $\ensuremath{\mathsf{NA}}\xspace$ not applicable due to use of product. NPD: No Performance Determined.

Note 1: This product does not contain asbestos or tar constituents.

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

/the

Signed for and on behalf of the manufacturer by: Peter Fleischmann (Managing Director) Paris 10/08/2018