

Declaration of Performance

ROLLSTICK 31 ALPA

1. Identification code	ROLLSTICK 31 ALPA
2. Intended use	Bitumen air and water vapour control layers
3. Manufacturer	AXTER SAS, 143 avenue de Verdun, 92130 Issy-les-Moulineaux, 75016 PARIS, France www.axter.eu/dop
4. Authorised representative	N/A
5. System of assessment and verification of constancy of performance of the product	System 3
6a. Product covered by the harmonised standard:	EN 13970 Declaration of the performance of the essential characteristics by the manufacturer
6b. European Technical Assessment:	N/A

7. Declared performance

Essential characteristics			Performance				Harmonised technical specification
			Value	Tolerance		Units	
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal		80	50	150	N	EN 13970:2005/ A1:2007
	Cross direction		80	50	150		
Tensile properties: maximum tensile force	Longitudinal		250	200	550	N/50 mm	
	Cross direction		150	120	350		
Tensile properties: elongation	Longitudinal		3	2	4	%	
	Cross direction		3	2	4		
Shear resistance of joint	Maximum force	Selvage	PND	-	-	N/50mm	
		End joint	PND	-	-		
Flexibility at low temperature			-14	≤		°C	
Resistance to impact			500			mm	
Watertightness under 2 kPa			NA			-	
Water vapour transmission properties			285			m	
Durability EN 1296	Water vapour transmission		290			m	
Durability EN 1847	Water vapour transmission		PND			m	
Reaction to fire			PND			-	
Dangerous substances			Note 1 and 2			-	

NA: not applicable due to use of product. PND: Performance not determined.

Note 1 : This product does not contain asbestos or tar constituents.

Note 2 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)



Paris
10/08/2018