

Declaration of Performance

VAP IND

1. Identification code	VAP IND
2. Intended use	Bitumen air and water vapour control layers
3. Manufacturer	AXTER SAS 143, avenue de Verdun, 92130 Issy-les-Moulineaux, France www.axter.co.uk/downloads
4. Authorised representative	NA
5. System of assessment and verification of	System 3
6a. Product covered by the harmonised standard:	EN 13970 Declaration of the performance of the essential characteristics by the manufacturer
6b. European Technical Assessment :	NA

7. Declared performance

Essential characteristics			Performance			Harmonised technical specification	
			Value	Tolerance			Units
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal	20	≥		N	EN 13970:2005/ A1:2007	
	Cross direction	20	≥				
Tensile properties : maximum tensile force	Longitudinal	200	≥		N/50 mm		
	Cross direction	200	≥				
Tensile properties : elongation	Longitudinal	20	≥		%		
	Cross direction	20	≥				
Shear resistance of joint	Maximum force	Selvedge	200	≥			N/50mm
		End joint	200	≥			
Flexibility at low temperature			-20	≤			°C
Resistance to impact			300	≥			mm
Watertightness under 2 kPa			Conform				-
Water vapour transmission properties			1500	≥			m
Durability EN 1296	Water vapour transmission		750	≥			m
Durability EN 1847	Water vapour transmission		PND				m
Reaction to fire			E				-
Dangerous substances			Note 1 and 2			-	

NA: not applicable due to use of product.

Note 1 : This product does not contain asbestos or tar constituents

Note 2 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Chairman)



Paris
10/08/2018