

Technical Data Sheet

MASTIC HYRENE Adhesive

| | |
|---------------------------|--|
| Description | MASTIC HYRENE is a cold applied bituminous adhesive with added solvents. |
| Usage | <p>Adhesive (spots or strips) for thermal insulation boards (PIR, PUR, EPS) - 500g/m², to be increased according to wind load - under non ballasted and ballasted waterproofing systems.</p> <p>Used for partially bonding waterproofing membranes with sanded under surface on to concrete decks.</p> <p>Cleaning tools: petroleum solvents (eg. White Spirit)</p> |
| Packaging | 25 kg drums with plastic lining bag inside. |
| Storage | <p>Store in a cool ventilated area.</p> <p>Protect from heat and keep away from any source of flame or spark.</p> <p>Maximum storage period : 2 years (in unopened original packaging).</p> |
| Safety Information | <p>This product contains flammable products.</p> <p>Safety precautions to be taken when using this product are described in the MASTIC HYRENE safety data sheet.</p> |

| Characteristics | Method | Units | Values | Tolerance |
|--------------------|--------|-------|--------------------|-----------|
| Density | | | 1.2 | ± 0.05 |
| Solid content | | % | 87 | ± 2 |
| Viscosity at 25 °C | T6V10 | cps | 40 000 to 50 000 | |
| Colour | | | Black | |
| Consistency | | | Smooth semi-liquid | |

The manufacturer reserves the right to modify, at any time, the characteristics of this product.