

# Product Data Sheet

## TIMBER DECKING SUPPORT ADAPTER

**For wood decking on flat roof amenity areas, Axter offers a timber decking support attachment that fits directly on to the wings of the Axter fixed/adjustable paving slab supports\* without the need for fixings or adhesive. This accessory is designed to support a timber bearer or joist onto which the decking can be fastened.**

This Timber Decking Support Adapter enables easy installation of flat decking over a laid to falls flat roof. The joists are held clear of the roof itself, increasing their life and allowing free passage of water to outlets.

\*See Product Data Sheet on Axter Paving Slab Supports (polypropylene).



### Key benefits

- Easily fitted to Axter's polypropylene Paving Slab Supports, both fixed and adjustable.
- Perforations in the head prevent water stagnation and prolong the life of timber decking.
- High resistance to deformation.
- Corrosion and maintenance free.
- Easy transport, storage and installation.

## Product description and packaging

Timber Decking Support Adapter	
Diameter	120mm
Overall height	60mm
Base height	25mm
Packaging	120 units/box

Perforations in the head prevent water stagnation at the points of contact with the timber joist, prolonging the life of the timber decking.

## Installation

The Timber Decking Support Adapters are designed to fit easily on to the wings of Axter's paving slab supports which are available in the following sizes:

- Fixed: 8mm; 20mm
- Adjustable: 25-40mm, 40-60mm, 60-90mm, 90-150mm, 150-260mm

The joist is mechanically fixed at right angles to the oblong holes in the support head.

The adapters can be used in the following temperature range: -30°C to +50°C.

## Composition

Copolymer polypropylene with calcium carbonate (CaCO<sub>3</sub>).

## Storage

Store in a cool place, away from heat.

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at [www.axter.co.uk/downloads](http://www.axter.co.uk/downloads). Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: [technical@axterltd.co.uk](mailto:technical@axterltd.co.uk), telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.

