





According to Regulation (EC) No. 1907/2006, Annex II, as amended by Regulation (EU) No. 453/2010

SGCA - SPRAY GUN CLEANING AEROSOL

Adhesive Accessory

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name SPRAY GUN CLEANING AEROSOL

Product number SGCA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Uses advised againstNo specific uses advised against are identified.

11.3 Details of the supplier of the safety data sheet

Supplier: Axter Ltd, Harbour Landing, Fox's Marina,

The Strand, Wherstead, Ipswich IP2 8NJ

Tel: +44 (0) 1473 724056 Email: info@axterltd.co.uk Website: www.axter.co.uk

1.4 Emergency telephone: Axter Ltd - +44 (0) 1473 724056

(this line is open from 8.00 am to 5.30 pm, Monday to Friday). In the event of a medical enquiry involving this product, members of

the public should contact:

NHS 111 a doctor or

a local hospital accident and emergency department.

The NPIS (National Poisons Information Service) helpline is available

for enquiries from medical professionals only.

Tel: 0344 892 0111

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Carc. 2 - H351 STOT SE 3 - H336

Environmental hazards Not Classified

Human health Vapours/aerosol spray may irritate the respiratory system.

Physicochemical Aerosol containers can explode when heated, due to excessive pressure

build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. The product is extremely flammable.

2.2 Label elements

Pictogram





Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness. H351 Suspected

of causing cancer.

Precautionary statements

A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. A2 Do not spray on a naked flame or any incandescent material.

A3 Keep away from sources of ignition - No smoking.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Do not

pierce or burn, even after use. P260 Do not breathe vapours.

P281 Use personal protective equipment as required.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. P501 Dispose of contents/ container in accordance with

national regulations.

RCH002a Restricted to professional users.

Contains DICHLOROMETHANE

2.3 Other hazards

Section 3: Composition/information on ingredients

3.2 Mixtures

DICHLOROMETHANE			60-100%
CAS number: 75-09-2	EC number: 200-838-9	REACH registration number: 01-2119480404-41-0007	
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Carc. 2 - H351 STOT SE 3 - H336			
BUTANE			10-30%
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: 01-2119474691-32-0000	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280			
PROPANE			10-30%
CAS number: 74-98-6	EC number: 200-827-9	REACH registration number: 01-2119486944-21-0000	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280			

The full text for all hazard statements is displayed in Section 16.

Section 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected p	person from source of	contamination.
---------------------	-------------------	-----------------------	----------------

Inhalation Move affected person to fresh air at once. Get medical attention if any

discomfort continues.

Ingestion DO NOT induce vomiting. Get medical attention immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and

water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses

and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this

Safety Data Sheet to the medical personnel.

4.2 Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the

concentration and the length of exposure.

Inhalation Irritation of nose, throat and airway. Coughing, chest tightness, feeling of

chest pressure.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Vapour, spray or dust may cause chronic eye irritation or eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctorNo specific recommendations. If in doubt, get medical attention promptly.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazardsContainers can burst violently or explode when heated, due to excessive

pressure build-up. Extremely flammable.

Hazardous combustion

products Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during

firefighting Containers close to fire should be removed or cooled with water. Do not

allow water to contact any leaked material.

Special protective

equipment for firefighters Wear chemical protective suit. Wear positive-pressure self-contained

breathing apparatus (SCBA) and appropriate protective clothing.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Absorb spillage

with non- combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material.

Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

Section 7: Handling and storage

7.1 Precautions for safe handling

Usage precautions Avoid inhalation of vapours and spray/mists. Avoid contact with skin and

eyes. Do not use in confined spaces without adequate ventilation and/ or respirator. Spraying is permitted only in closed systems, spray cabinets

or spray boxes with adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Section 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits DICHLOROMETHANE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 350 mg/m 3 Short-term exposure limit (15-minute): WEL 300 ppm 1060 mg/m 3 Sk

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

DICHLOROMETHANE (CAS: 75-09-2)

Ingredient comments WEL = Workplace Exposure Limits

DNEL Consumer - Dermal; Short term systemic effects: 353 mg/m³

Workers - Dermal; Short term systemic effects: 706 mg/m³

PNEC Fresh water; 0.54 mg/l

Sediment (Freshwater); 4.47 mg/kg Intermittent release; 0.27 mg/l Sediment (Marinewater); 1.61 mg/kg

Marine water; 0.194 mg/l

STP; 26 mg/l Soil; 0.583 mg/kg

8.2. Exposure controls

Protective equipment









Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash hands after handling. When using do not eat,

drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly- ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type AX. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Environmental exposure controls

Keep container tightly sealed when not in use.

Section 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

ColourVarious colours.OdourCharacteristic.Odour thresholdNot available.pHNot available.Melting pointNot available.Initial boiling point and range39-40C°C @

Flash point <40°C

Evaporation rateNot available.Evaporation factorNot available.Flammability (solid, gas)Not available.

Upper/lower flammability

or explosive limits Lower flammable/explosive limit: 1.8

Upper flammable/explosive limit: 9

Other flammabilityNot available.Vapour pressureNot available.Vapour densityNot available.

Relative density @ 20°C

Bulk density Not available.

Solubility(ies) Insoluble in water.

Partition coefficient Not available.

Decomposition Temperature Not available.

Viscosity 20-50 mPa s @ 25°C

Explosive properties Not available.

Explosive under the

influence of a flame Not considered to be explosive.

Oxidising properties Not available.

Comments Information given is applicable to the product as supplied.

9.2. Other information

Other information No information required.

Refractive index
Not available.

Particle size
Not available.

Molecular weight
Not available.

Volatility
Not available.

Saturation concentration
Critical temperature
Not available.

Volatile organic compound This product contains a maximum VOC content of 798 g/litre.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions Not applicable. Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with water. Avoid heat, flames and other sources of ignition.

Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition

products Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral Acute toxicity oral

(LDso mg/kg) 2,000.0 Species Rat

ATE oral (mg/kg) 3,333.33

Acute toxicity - dermal Acute toxicity dermal

(LDso mg/kg) 2,000.0 Species Rat

Acute toxicity - inhalation

Species Rat

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Moderately irritating.

Respiratory sensitisation

Respiratory sensitisation Sensitising.

Carcinogenicity

Carcinogenicity Suspected carcinogen based on limited evidence.

Target organ for carcinogenicity

Reproductive toxicity

Reproductive toxicity - development

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Morphological changes that are potentially reversible but provide clear

evidence of marked organ dysfunction.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical

structure.

Inhalation Irritating to respiratory system. May cause sensitisation by inhalation.

Ingestion May cause stomach pain or vomiting.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritation of eyes and mucous membranes.

Acute and chronic

health hazards May cause sensitisation by skin contact. The product contains small

quantities of isocyanate. May cause respiratory allergy. May cause respiratory system irritation. May cause respiratory system irritation. Frequent inhalation of vapours may cause respiratory allergy.

Route of entry Inhalation Skin and/or eye contact

Medical symptoms Irritation of eyes and mucous membranes. Coughing, chest tightness,

feeling of chest pressure.

Medical considerations Chronic respiratory and obstructive airway diseases. Toxicological

information on ingredients.

DICHLOROMETHANE

Toxicological effectsThe toxicity of this substance has been assessed during REACH

registration.

Acute toxicity - oral Acute toxicity oral

(LDso mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 2,000.0

Acute toxicity - dermal Acute toxicity dermal

(LDso mg/kg) 2,000.0

Species Rat

Acute toxicity - inhalation Acute toxicity inhalation

(LCso vapours mg/l) 86.0 Species Rat

ATE inhalation

(vapours mg/l) 86.0

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin., REACH dossier information.

Serious eye damage/irritation

Serious eye damage/irritation Causes eye irritation.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Positive. **Genotoxicity - in vivo** Negative.

Carcinogenicity

IARC carcinogenicityIARC Group 2B Possibly carcinogenic to humans.

Reproductive toxicity Reproductive toxicity -

fertility No evidence of reproductive toxicity in animal studies.

Reproductive toxicity -

development No evidence of reproductive toxicity in animal studies.

BUTANE

Acute toxicity - inhalation Acute toxicity inhalation

(LCso gases ppmV) 658,000.0

Species Rat

ATE inhalation (gases ppm) 658,000.0

Section 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Acute toxicity - fish LC_{50} , 96 hours: > 193 mg/l, Freshwater fish

LC₅₀, 96 hours: > 97 mg/l, Marinewater fish

Acute toxicity - aquatic

invertebrates EC_{50} , 48 hours: > 27 mg/l,

EC₅₀, 48 hours: >500 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 550 mg/l, Algae

Ecological information on ingredients.

DICHLOROMETHANE

Acute toxicity - fish LC50, 96 hours: 193 mg/l, Pimephales promelas (Fat-head Minnow)

LC50, 48 hours: 97 mg/l, Fundulus heteroclitus

Acute toxicity - aquatic

invertebrates EC50, 48 hours: 27 mg/l, Daphnia magna

LC₅₀, 48 hours: 109 mg/l, Palaemonetes pugio

Acute toxicity -

aquatic plants NOEC, 192 hours: 550 mg/l, Microcystis aeruginosa - Algae, blue,

cyanobacteria

Acute toxicity -

microorganisms EC₅₀, 0.67 hours: 2590 mg/l, Bacteria

Chronic toxicity -

fish early life stage NOEC, 28 days: 83 mg/l, Pimephales promelas (Fat-head Minnow)

BUTANE

Acute toxicity - fish LCo, 96 hours: 24,11 mg/l, Fish

Acute toxicity - aquatic

invertebrates LCo, 48 hours: 14,22 mg/l, Daphnia magna

Acute toxicity - aquatic

plants LCo, 96 hours: 7,71 mg/l, Algae

PROPANE

Acute toxicity - fish LCo, 96 hours: 24 mg/l, Fish

Acute toxicity - aquatic

invertebrates LCo, 48 hours: 7 mg/l, Daphnia magna

Acute toxicity - aquatic

plants LCo, 96 hours: 8 mg/l,

12.2. Persistence and degradability

Persistence and

degradability The product is not readily biodegradable.

Stability (hydrolysis) Reacts with water.

Biological oxygen demand < 10 g O₂/g substance

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected

to be bioaccumulating.

Partition coefficient Not available.

Ecological information on ingredients.

DICHLOROMETHANE

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will

evaporate easily from all surfaces.

Ecological information on ingredients.

DICHLOROMETHANE

Mobility The product contains volatile organic compounds (VOCs) which will

evaporate easily from all surfaces.

Ecological information on ingredients.

DICHLOROMETHANE

Mobility The product contains volatile organic compounds (VOCs) which will

evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and

vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

DICHLOROMETHANE

Results of PBT and vPvB

assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Ecological information on ingredients.

DICHLOROMETHANE

Other adverse effects Not applicable.

Section 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed

waste disposal site in accordance with the requirements of the local Waste

Disposal Authority.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the

requirements of the local Waste Disposal Authority.

Section 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name

(ADR/RID) AEROSOLS

Proper shipping name

(IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID subsidiary risk 6.1

ADR/RID label 2.1 & 6.1

IMDG class 2.1

IMDG subsidiary risk 6.1

ICAO class/division 2.1

ICAO subsidiary risk 6.1

Transport labels





14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Pollution Act 1974.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Guidance The spraying of flammable liquids HSG178.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Section 16: Other information

Revision date 26/09/2024

Revision 22

Supersedes date 03/11/2020

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

Store Between Store Between 5°C - 25°C

Contains SVHC NO

The data contained in this SDS has been supplied as required by the EC REACH Regulation No. 1907/2006 and the EC Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided. Please ensure that it is passed to the appropriate person(s) in your company who are capable of acting on the information.

Disclaimer:

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. The user should ensure all necessary precautions are taken during handling, storage, installation and disposal of the product, and all regulations to guarantee safety of people and the environment are observed. Axter Ltd accepts no liability for non-compliant use of this product.