

Safety Data Sheet

According to 1907/2006/EC, Article 31

STARCOAT PMMA M PRIMER

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: STARCOAT PMMA M PRIMER

1.2 Relevant identified uses of the substance or mixture and uses advised against See Section 16

Application of the substance / the mixture Priming

1.3 Details of the supplier of the safety data sheet

Supplier:

Axter Ltd, Harbour Landing, Fox's Marina,
The Strand, Wherstead, Ipswich IP2 8NJ
Tel: +44 (0) 1473 724056
Email: info@axterltd.co.uk
Website: www.axter.co.uk

1.4 Emergency telephone:

Axter Ltd - +44 (0) 1473 724056
(this line is open from 8.00 am to 5.30 pm, Monday to Friday).
In the event of a medical enquiry involving this product, members of the public should contact:
NHS 111
a doctor or
a local hospital accident and emergency department.
The NPIS (National Poisons Information Service) helpline is available for enquiries from medical professionals only.
Tel: 0344 892 0111

Section 2: Hazards identification*2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit 2. H319 Causes serious eye irritation
STOT SE3 H336 May cause drowsiness or dizziness**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02



GHS07

Signal word Danger Hazard determining components of labelling: 2-methoxy-1-methylethyl acetate**Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P280 Wear protective gloves/ eye protection.

P312 Call a Poison Centre/ doctor if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).**vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

Section 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
CAS: 108-65-6 EINECS: 203-603-9 Reg no 01-2119475791-29-0001	2-methoxy-1-methylethyl acetate	Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
CAS: 141-78-6 EINECS: 205-500-4 Reg no 01-2119475103-46	ethyl acetate	Flam. Liq. 2, H225; Eye Irrit. 2, H319 STOT SE 3, H336	10-25%

Additional information: For the wording of the listed risk phrases refer to section 16.

Section 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.
Take affected persons out of danger area and lay down.
Involve doctor immediately.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
Seek medical treatment.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Skin sensitization; Irritant to skin, eyes, respiratory system

*Section 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, sand, extinguishing powder, foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released:
Carbon monoxide (CO) Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.
Wear self-contained respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Section 6: Accidental release measures*6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation



Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7: Handling and storage*7.1 Precautions for safe handling**

Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient heat. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.

Do not refill residue into storage receptacles.

Ensure good ventilation/exhaustion at the workplace.

At least 7-fold air changes

Prevent formation of aerosols.

Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Only explosion-proof equipment.

Protect against electrostatic charges.

Protect from heat.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

Information about storage in one common storage facility:

Store away from oxidising agents.
Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Storage in a collecting room is required.
Store under lock and key and with access restricted to technical experts or their assistants only.
Max storage temperature 30°C.
Keep container tightly sealed.
Protect from heat and direct sunlight.

7.3 Specific end use(s) Building coating or sealing.***Section 8: Exposure controls/personal protection**

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
108-65-6 2-methoxy-1-methylethyl acetate (10-<25%)		
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk	
141-78-6 ethyl acetate (10-<20%)		
WEL	Short-term value: 1468 mg/m ³ Long-term value: 734 mg/m ³	
DNELs		
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	DNEL (population)	1.67 mg/kg bw/day (Long-term - systemic effects)
Dermal	DNEL (worker)	153.5 mg/kg bw/day (Long-term - systemic effects)
Inhalative	DNEL (population)	33 mg/m ³ (Long-term - systemic effects)
	DNEL (worker)	275 mg/m ³ (Long-term - systemic effects)
141-78-6 ethyl acetate		
Oral	DNEL (population)	4.5 mg/kg bw/day (Long-term - systemic effects)
	DNEL	63 mg/kg bw/day (Long-term - systemic effects)
Inhalative	DNEL (population)	37 mg/m ³ (Long-term - systemic effects)
	DNEL (population)	734 mg/m ³ (Acute - local effects)
		734 mg/m ³ (Acute - systemic effects)
		367 mg/m ³ (Long-term - systemic effects)
		367 mg/m ³ (Long-term - local effects)
		1468 mg/m ³ (Acute - local effects)
		1468 mg/m ³ (Acute - systemic effects)
	DNEL (worker)	734 mg/m ³ (Long-term - systemic effects) 734 mg/m ³ (Long-term - local effects)
PNECs		
108-65-6 2-methoxy-1-methylethyl acetate		
PNEC	0.0635 mg/l (seawater) 0.635 mg/l (freshwater)	

141-78-6 ethyl acetate

PNEC	0.22 mg/kg (ground) 0.34 mg/kg (sediment) 0.26 mg/l (water)
------	---

Additional information: The lists valid at the time were used as the basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures: Avoid contact with eyes and skin. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes.

Respiratory protection:

Ensure good ventilation.

In interiors and where inhalation exceeds limits: Filter type A1 using an air recycling independent breathing apparatus at high concentrations, A2 at an intensive or longer outline.

Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Check that protective gloves are in good condition prior to each use.

Glove material has to be impermeable and resistant to the product/substance/preparation. Selection of the glove material must take account of penetration times, rates of diffusion and degradation.

Due to lack of tests, no recommendation regarding the glove material can be given for the product/ the preparation/ the chemical mixture.

Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Protective gloves must comply with EN 374. Suitable material: nitrile.

Penetration time of glove material

Our recommendation is mainly for a one-time use of the gloves as short-term protection against liquid splashes. For other applications, you should contact a glove manufacturer. The exact break through time must be found out from the manufacturer of the protective gloves and must be observed.

For permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Butyl rubber, BR

For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR Not suitable are gloves made of the following material: Leather

Eye protection:



Tightly sealed goggles

EN-Standard: EN 166

Body protection:



Protective work clothing

Section 9: Physical and chemical properties*9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Fruit-like
Odour threshold:	Not determined.
pH-value:	Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	77°C (Ethylacetat)
Flash point:	5°C (EN ISO 3680)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	315°C (1-Methoxy-2-propylacetat)
Self-igniting:	Product is not self igniting.
Explosive properties:	Not determined.

Explosion limits:

Lower:	2.1 Vol % (Ethylacetat)
Upper:	11.5 Vol % (Etylacetat)
Vapour pressure at 20°C:	4.9 hPa (Ethylacetat)
Density at 20°C:	1.51 g/cm ³ (EN ISO 2811-1)
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Fully miscible.
Partition coefficient (n-octanol/water):	Not determined.

Viscosity:

Dynamic at 20 °C:	2000 mPas (EN ISO 2555)
-------------------	-------------------------

Solvent content:

Organic solvents:	36.5%
VOC (EC)	36.49%
Solids content:	62-66%

9.2 Other information No further relevant information available.

***Section 10: Stability and reactivity**

10.1 Reactivity see Section 10.2

10.2 Chemical stability**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Exothermic reaction.

Reacts with peroxides and other radical forming substances.

A hazardous polymerization may occur after the exhaustion of the inhibitor.

10.4 Conditions to avoid: Heat and direct sunlight.

10.5 Incompatible materials: Reaction with peroxides and other free-radical generators.

10.6 Hazardous decomposition products:

No dangerous decomposition when product used according to specifications.

Additional information:

Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan at the workplace where the product is present.

***Section 11: Toxicological information**

11.1 Information on toxicological effects There were no toxicological findings to the mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Inhalative	LC50/4h	91.5 mg/l (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8500 mg/kg (rat)
Dermal	LC50	5.000 mg/kg (rat)
Inhalative	LC50/4h	35.7 mg/l (rat)
141-78-6 ethyl acetate		
Oral	LD50	4934 mg/kg (rabbit) (OECD 401)
Dermal	LC50	>18000 mg/kg (rat)
	LD50	> 18000 mg/kg (rabbit)
Inhalative	LC50/4h	56 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Other information (about experimental toxicology):

Due to the high vapour pressure a harmful concentration in the air is quickly reached. At high concentrations a narcotic effect can occur.

Subacute to chronic toxicity: not tested

Repeated dose toxicity no data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) not tested

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

*Section 12: Ecological information

12.1 Toxicity

Aquatic toxicity:	
108-65-6 2-methoxy-1-methylethyl acetate	
EC50/48h	> 500 mg/l (daphnia magna)
LC50/96h	100 - 180 mg/l (Rainbow trout)
141-78-6 ethyl acetate	
EC50/24h	3090 mg/l (daphnia magna) (DIN 38412, Part 11)
EC50/48h	164 mg/l (daphnia magna)
	3300 mg/l (scenedesmus subspicatus)
LC50/96h	230 mg/l (fish)
	455 mg/l (pimephales promelas)
NOEC/21d	2.4 mg/l (daphnia magna)
NOEC/72h	>100 mg/l (Alge (Desmodesmus subspicatus)) (OECD 201)

12.2 Persistence and degradability Easily biodegradable

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

vPvB: Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

12.6 Other adverse effects No further relevant information available.

*Section 13: Disposal considerations

13.1 Waste treatment methods

Hazardous waste according to Waste Catalogue (EW C). If recycling is not possible, waste must be removed in compliance with local regulations.

Recommendation

Uncured product residues are special waste.

Cured product residues are not hazardous waste.



Must not be disposed together with household rubbish. Do not allow product to reach sewage system. Uncured product residues are special waste. Cured product residues are not hazardous waste.

Waste disposal key:

The following Waste Codes of the European Waste Catalogue (EWC), are considered a recommendation. The disposal must be coordinated with the local waste disposal company.

Liquid product:

080111 * paint and varnish containing organic solvents or other dangerous substances

080199 waste nec

Cured product residues:

080112 paint and varnish wastes other than those mentioned in 080111

080410 adhesive waste adhesives and sealants other than those mentioned in 080409

European waste catalogue 080111 * (recommended)


Uncleaned packaging:

Recommendation:

This material and its container must be disposed of as hazardous waste. Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

***Section 14: Transport information**

14.1	UN-Number ADR, IMDG, IATA	UN1263
14.2	UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3	Transport hazard class(es) ADR, IMDG, IATA	
	Class Label	3 Flammable liquids. 3
14.4	Packing group ADR, IMDG, IATA	III
14.5	Environmental hazards: Marine pollutant:	No
14.6	Special precautions for user Danger code (Kemler): EMS Number: Stowage category:	Warning: Flammable liquids. --- F-E,S-E A
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
	Transport/Additional information:	
	ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	Transport category Tunnel restriction code	3 E
	Remarks:	Classification according to viscosity clause (2.2.3.1.4)
	IMDG Limited quantities (LQ)	5L

Excepted quantities (EQ) Code:	E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Classification according to viscosity clause (2.3.2.3)
Remarks:	
UN "Model Regulation":	UN 1263 PAINT, 3, III

*Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5000t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000t

REGULATION (EC) No. 1907/2006 ANNEX XVII Conditions of restriction 3

National regulations:

Information about limitation of use:

Employment restrictions under the Maternity Protection Directive (94/33/EC).

Employment restrictions for maternity Directive (92/85/EEC) for expectant and nursing mothers.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*Section 16: Other information

These figures relate to the product as delivered.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H319 Causes serious eye irritation.

Training hints

Teaching on hazards and precautions must take place before the start of employment and at last annually thereafter.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Eye Irrit. 2: Serious eye damage / eye irritation - Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Sources:

www.gestis.de
www.echa.eu
logkow.cisti.nrc.ca

*** Data compared to the previous version altered.**

The information provided in this document is accurate to the best of our knowledge. The document does not constitute a specification and Axter takes no responsibility for the suitability of the product in a particular use. It is the user's responsibility to ensure that the product is suitable for the intended application and use and to take the necessary precautions to ensure that during handling, storage and installation of the product, all regulations to guarantee safety of people and the environment are observed. For further information or technical design assistance, contact Axter Ltd.

The data contained in this SDS has been supplied as required by the EC REACH Regulation No. 1907/2006 and the EC Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided. Please ensure that it is passed to the appropriate person(s) in your company who are capable of acting on the information.

Disclaimer:

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. The user should ensure all necessary precautions are taken during handling, storage, installation and disposal of the product, and all regulations to guarantee safety of people and the environment are observed. Axter Ltd accepts no liability for non-compliant use of this product.