

Safety Data Sheet

REACH regulation (EC) 1907/2006 - 2020/878

WILOTEKT SURFACE CONDITIONING PRIMER

Primer

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Wilotekt Surface Conditioner (Primer - Grundierung) for Wilotekt Plus hot melt waterproofing system

Product code: 1534997

1.2. Relevant identified uses of the substance or mixture and uses advised against

Sealing bituminous coating.

Professional use only.

1.3. Details of the supplier of the safety data sheet

Supplier

Axter Ltd, Harbour Landing, Fox's Marina,

The Strand, Wherstead, Ipswich IP2 8NJ

Tel: +44 (0) 1473 724056

Email: info@axterltd.co.uk

Website: www.axter.co.uk

1.4. Emergency telephone

Axter Ltd - +44 (0) 1473 724056

(this line is open from 8.00 am to 5.30 pm, Monday to Friday).

In the event of a medical enquiry involving this product, members of the public should contact:

NHS 111

a doctor or

a local hospital accident and emergency department.

The NPIS (National Poisons Information Service) helpline is available for enquiries from medical professionals only.

Tel: 0344 892 0111

Section 2: Hazards identification

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Acute dermal toxicity, Category 4 (Acute Tox. 4, H312).

Acute inhalation toxicity, Category 4 (Acute Tox. 4, H332).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

Specific target organ toxicity (repeated exposure), Category 2 (STOT RE 2, H373).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS07



GHS08



GHS02

Signal Word:

WARNING

Product identifiers:

EC 215-535-7

XYLENE

Hazard statements:

H226

Flammable liquid and vapour.

H312 + H332

Harmful in contact with skin or if inhaled.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

H373

May cause damage to organs (liver, kidneys, central nervous system) through prolonged or repeated exposure (if inhaled, if swallowed, in contact with skin).

Precautionary statements - Prevention:

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260

Do not breathe vapours.

P264

Wash hands thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - Response:

P302 + P352

IF ON SKIN: Wash with plenty of soap and water.

P304 + P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P314

Get medical advice/attention if you feel unwell.

P332 + P313

If skin irritation occurs: Get medical advice/attention.

P337 + P313

If eye irritation persists: Get medical advice/attention.

P362 + P364
P370 + P378

Take off contaminated clothing and wash it before reuse.
In case of fire: Use dry powder for extinction

Precautionary statements - Disposal:
P501

Dispose of contents/container to an approved site as a
hazardous material.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006. The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

Section 3: Composition/information on ingredients

3.2. Mixtures

Some substances are in composition because they have VLEP by inhalation:

- CAS: 232-490-9 BITUMEN

However, they are safe in this mixture because the VLEP concern hot bitumen vapours. This product is not affected by this hazard.

Composition:

Identification	(EC) 1272/2008	Note	%
CAS: 8052-42-4 EC: 232-490-9 REACH: 01-2119480172-44 BITUMEN		[1]	50 \leq x % < 100
CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32 XYLENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	C [1]	25 \leq x % < 50
INDEX: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 ETHYLBENZENE	GHS02, GHS07, GHS08 Dgr Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 Asp. Tox. 1, H304	[1]	2.5 \leq x % < 10
INDEX: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH: 01-2119471310-51 TOLUENE	GHS02, GHS08, GHS07 DRG Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336	[1] [2] [XV11]	0 \leq x % < 2.5

INDEX: 603-001-00-X CAS: 67-56-1	GHS02, GHS06, GHS07 DRG	[1] [XV11]	0 <= x % < 2.5
EC: 200-659-6	Flam. Liq. 2, H225		
REACH: 01-2119433307-44	Repr. 2, H361d		
METHANOL	Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 STOT SE 1, H370		

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32 XYLENE		oral: ATE = 3523 mg/kg BW
INDEX: 603-001-00-X CAS: 67-56-1 EC: 200-659-6 REACH: 01-2119433307-44 METHANOL	STOT SE 1 (Cut) : H370 C>= 10% STOT SE 2: H371 3% <= C < 10% STOT SE 1 (Oral) : H370 C>= 10% STOT SE 2: H371 3% <= C < 10% STOT SE 1 (Inh) : H370 C>= 10% STOT SE 2: H371 3% <= C < 10%	

Information on ingredients:

(Full text of H-phrases: see section 16)

[XVII] Restricted substance under Regulation (EC) No. 1907/2006 (REACH), Annex XVII.

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

Section 4: First aid measures

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation:**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not proceed with mouth-to-mouth or mouth-to-nose resuscitation. Use the appropriate equipment.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, especially if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner. Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital. Remove the contaminated clothing and wash the skin thoroughly with soap and water or a recognized cleaner. DO NOT use solvents or diluents.

In the event of swallowing:

Do not give the patient anything orally.
Keep the person exposed at rest. Do not force vomiting.
Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

Section 5: Firefighting measures

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:
water with AFFF (Aqueous Film Forming Foam) additive
foam
multipurpose ABC powder
Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use:
water jet
water

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed:
carbon monoxide (CO)
carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Section 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.
Avoid inhaling the vapours.
Avoid any contact with the skin and eyes.
If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures.

Use drums to dispose of collected waste in compliance with current regulations.

Do not discard rinsing agents down the drain.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

Section 7: Handling and storage

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapour concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear anti-static shoes and clothing and make floors non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected. Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks.

Do not smoke. Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not inhale vapours.

Avoid inhaling vapours. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapour extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions. In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging:

Vats

Drums

Suitable packaging materials:

Metal

Unsuitable packaging materials:

Plastic

7.3. Specific end use(s)

No data available.

Section 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits:**

European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

CAS	VME-mg/m ³	VME-ppm	VLE-mg/m ³	VLE-ppm	Notes
1330-20-7	221	50	442	100	Skin
100-41-4	442	100	884	200	Skin
108-88-3	192	50	384	100	Skin
67-56-1	260	200	-	-	Skin

ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS	TWA	STEL	Ceiling	Definition	Criteria
8052-42-4	0.5 (l) mg/m ³			A4; BEIP	
1330-20-7	100 ppm	150 ppm		A4; BEI	
100-41-4	20 ppm			A3; BEI	
108-88-3	20 ppm			A4; BEI	
67-56-1	200 ppm	250 ppm		Skin; BEI	

Germany - AGW (BAuA - TRGS 900, 02/2022):

CAS	VME-ppm:	VME-mg/m ³ :	VLE-ppm:	VME-mg/m ³ :	Notes	TMP No:
1330-20-7	50	221	100	442	*	4 Bis. 84. *
100-41-4	20	88.4	100	442	*	84
108-88-3	20	76.8	100	384	R2 *	4bis.84
67-56-1	200	260	1000	1300	(12)	84
1330-20-7		50 ppm 220 mg/m ³			2(II)	
100-41-4		20 ppm 88 mg/m ³			2(II)	
108-88-3		50 ppm 190 mg/m ³			2(II)	
67-56-1		200 ppm 270 mg/m ³			4(II)	

France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

CAS	TWA	STEL	Ceiling	Definition	Criteria
8052-42-4	5 mg/m ³	10 mg/m ³			
1330-20-7	50 ppm 220 mg/m ³	100 ppm 441 mg/m ³		Sk, BMGV	
100-41-4	100 ppm 441 mg/m ³	125 ppm 552 mg/m ³		Sk	
108-88-3	50 ppm 191 mg/m ³	100 ppm 384 mg/m ³		Sk	
67-56-1	200 ppm 266 mg/m ³	250 ppm 333 mg/m ³		Sk	

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

XYLENE (CAS: 1330-20-7)

Final use:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Final use:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

BITUMEN (CAS: 8052-42-4)

Final use:

Exposure method:

Potential health effects:

DNEL:

Predicted no effect concentration (PNEC):

XYLENE (CAS: 1330-20-7)

Environmental compartment:

PNEC:

Environmental compartment:

PNEC:

Environmental compartment:

PNEC:

Environmental compartment:

PNEC:

Workers.

Dermal contact.

Long term systemic effects.

180 mg/kg body weight/day

Inhalation.

Short term systemic effects.

289 mg of substance/m³

Inhalation.

Short term local effects.

289 mg of substance/m³

Inhalation.

Long term systemic effects.

77 mg of substance/m³**Consumers.**

Ingestion.

Long term systemic effects.

1.6 mg/kg body weight/day

Dermal contact.

Long term systemic effects.

108 mg/kg body weight/day

Inhalation.

Short term systemic effects.

174 mg of substance/m³

Inhalation.

Short term local effects.

174 mg of substance/m³

Inhalation.

Long term systemic effects.

14.8 mg of substance/m³**Workers.**

Inhalation.

Long term local effects.

2.9 mg of substance/m³

Soil.

2.31 mg/kg

Fresh water.

0.327 mg/l

Sea water.

0.327 mg/l

Intermittent waste water.

0.327 mg/l

Environmental compartment:	Fresh water sediment.
PNEC:	12.46 mg/kg
Environmental compartment:	Marine sediment.
PNEC:	12.46 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC:	6.58 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):



Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

Butyl Rubber (Isobutylene-isoprene copolymer)

Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN14605/A1 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Category:

FFP2

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

A2 (Brown)

Use an anti-spray filter FFP2 (white) if product application is realized with a manual gun

Section 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties General information:**

Physical state:	Viscous liquid.
Colour:	Unspecified.
Odour:	Not stated.
Melting point/melting range:	Not specified.
Freezing point/freezing range:	Not stated.
Boiling point/boiling range:	Not specified.
Flammability (solid, gas):	Not stated.
Explosive properties, lower explosivity limit (%)	Not stated.
Explosive properties, upper explosivity limit (%)	Not stated.
Flash point:	26°C
Self-ignition temperature:	Not specified.
Decomposition point/ decomposition range:	Not specified.
pH:	Not relevant.
pH (aqueous solution):	Not stated.
Viscosity:	Coupe ISO 6 (à 23°C) = 18s
Water solubility	Insoluble.
Fat solubility:	Not stated.
Partition coefficient: n-octanol/water:	Not stated.
Vapour pressure (50°C):	Below 110 kPa (1.10 bar).
Density:	0.94 g/cm ³
Vapour density:	Not stated:

9.2. Other information

VOC (g/l): 446

9.2.1 Information with regard to physical hazard classes

No data available.

9.2.2 Other safety characteristics

No data available.

Section 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

accumulation of electrostatic charges.

heating

flames and hot surfaces

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

carbon monoxide (CO)

carbon dioxide (CO₂)

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful in contact with skin.

Harmful by inhalation.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

May cause severe damage to organs in the event of repeated or prolonged exposure.

11.1.1. Substances Acute toxicity:

XYLENE (CAS: 1330-20-7)

Oral route: LD50 = 3523 mg/kg
Species : Rat

Dermal route: LD50 > 4200 mg/kg

BITUMEN (CAS: 8052-42-4)

Oral route: LD50 > 5000 mg/kg
Species: RatDermal route: LD50 > 2000 mg/kg
Species: RabbitInhalation route (Vapours): LC50 > 94.4 mg/l
Species: Rat**Specific target organ systemic toxicity - repeated exposure:**

XYLENE (CAS: 1330-20-7)

Oral route: $50 < C \leq 100$ mg/kg body weight/day
Duration of exposure: 90 daysDermal route: $100 < C \leq 200$ mg/kg body weight/day
Duration of exposure: 90 daysInhalation route (Vapours): $0.2 < C \leq 0.25$ mg/l/6hrs/day
Duration of exposure: 90 days**11.1.2. Mixture****Acute toxicity:**Dermal route: Harmful in contact with skin.
 $1,000 < LD50 \leq 2000$ mg/kgInhalation route (Vapours): Harmful by inhalation.
Duration of exposure: 4 h
 $10 < LC50 \leq 20$ mg/l**11.2. Information on other hazards****Monograph(s) from the IARC (International Agency for Research on Cancer):**

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 108-88-3 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 100-41-4 : IARC Group 2B : The agent is possibly carcinogenic to humans.

CAS 1330-20-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 8052-42-4 : IARC Group 2B : The agent is possibly carcinogenic to humans.

Section 12: Ecological information

12.1. Toxicity

12.1.1. Substances

XYLENE (CAS: 1330-20-7)

Fish toxicity:

NOEC > 1.3 mg/l

Species: Oncorhynchus mykiss

Crustacean toxicity:

EC50 = 1 mg/l

Species: Daphnia magna

Duration of exposure : 24 h

OECD Guideline 211 (Daphnia magna Reproduction Test)

NOEC = 1.17 mg/l

Species: Daphnia sp.

Duration of exposure: 7 days

Algae toxicity:

ECr50 = 2.2 mg/l

Species: Selenastrum capricornutum

Duration of exposure: 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

BITUMEN (CAS: 8052-42-4)

Fish toxicity:

NOEC >= 1000 mg/l

Duration of exposure: 21 days

12.1.2. Mixtures

Any leaks in drains or waterways has to be avoided.

12.2. Persistence and degradability

12.2.1. Substances

XYLENE (CAS: 1330-20-7)

Biodegradability:

Rapidly degradable.

BITUMEN (CAS: 8052-42-4)

Biodegradability:

No degradability data is available, the substance is considered as Not degrading quickly.

BCF = 25.9

Species: Oncorhynchus mykiss (Fish)

12.3. Bioaccumulative potential

12.3.1. Substances

XYLENE (CAS: 1330-20-7)

Bioaccumulation:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

Section 13: Disposal considerations

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company. Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Do not eliminate with household waste.

Do not discard rinsing agents down the drain.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste):

15 01 10 * packaging containing residues of or contaminated by dangerous substances

08 04 09 * waste adhesives and sealants containing organic solvents or other dangerous substances

Section 14: Transport information

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	L	367 650	E1	3	D/E
IMDG	Class	2 ^o Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	3	-	III	L	F-E, S-E	223 955	E1	Category A	-	
IATA	Class	2 ^o Label	Pack gr.	Passager	Passager	Cargo	Cargo	Note	EQ	
	3	-	III	355	L	366	L	A3 A72 A192	E1	
	3	-	III	Y344	L	-	-	A3 A72 A192	E1	

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

Classification:



3

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.
For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture contains at least one restricted substance under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>.

Please refer to Section 3 to identify the substance involved.

Particular provisions:

No data available.

15.2. Chemical safety assessment

No data available.

Section 16: Other information

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin
H312	Harmful in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

Abbreviations:

LD50: The dose of a test substance resulting in 50% lethality in a given time period.
LC50: The concentration of a test substance resulting in 50% lethality in a given period.
EC50: The effective concentration of substance that causes 50% of the maximum response.
ECr50: The effective concentration of substance that causes 50% reduction in growth rate.
NOEC: The concentration with no observed effect.
REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.
ATE: Acute Toxicity Estimate
BW: Body Weight
DNEL: Derived No-Effect Level
PNEC: Predicted No-Effect Concentration
CMR: Carcinogenic, mutagenic or reprotoxic.
UFI: Unique formulation identifier.
STEL: Shortterm exposure limit
TWA: Time Weighted Averages
TMP: French Occupational Illness table
TLV: Threshold Limit Value (exposure)
AEV: Average Exposure Value.
ADR: European agreement concerning the international carriage of dangerous goods by Road.
IMDG: International Maritime Dangerous Goods.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organisation
RID: Regulations concerning the International carriage of Dangerous goods by rail.
WGK: Wassergefährdungsklasse (Water Hazard Class).
GHS02: Flame
GHS07: Exclamation mark
GHS08: Health hazard
PBT: Persistent, bioaccumulable and toxic.
vPvB: Very persistent, very bioaccumulable.
SVHC: Substances of very high concern.

The data contained in this SDS has been supplied as required by the EC REACH Regulation No. 1907/2006 and the EC Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided. Please ensure that it is passed to the appropriate person(s) in your company who are capable of acting on the information.

Disclaimer:

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. The user should ensure all necessary precautions are taken during handling, storage, installation and disposal of the product, and all regulations to guarantee safety of people and the environment are observed. Axter Ltd accepts no liability for non-compliant use of this product.