

Safety Data Sheet

According to 1907/2006/EC, Article 31

STARCOAT PMMA ROLLER APPLIED SURFACING

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: STARCOAT PMMA ROLLER APPLIED SURFACING

1.2 Relevant identified uses of the substance or mixture and uses advised against See Section 16

Application of the substance / the mixture Sealing

1.3. Details of the supplier of the safety data sheet

Supplier

AXTER LTD, West Road, Ransomes Europark, Ipswich IP3 9SX UK

Tel: +44 (0) 1473 724056, 8.00 am to 5.30 pm, Monday to Friday

Email: info@axterltd.co.uk

1.4 Emergency telephone

+ 44 1473 724056 (NOT 24HRS - 8am - 5.30pm, Monday to Friday)

In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07

Signal word

Warning

Contains

Methyl methacrylate
2-ethylhexyl acrylate

Hazard statements

H226

Flammable liquid and vapour

H315

Causes skin irritation

H317

May cause an allergic skin reaction

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition surfaces. - No smoking.

P261

Avoid breathing vapours.

P280

Wear protective gloves/ eye protection.

P303+P361+P353

IF ON SKIN (or HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P312

Call a POISON CENTRE/ doctor if you feel unwell.

P403+P235

Store in a well-ventilated place. Keep cool.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT**

Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

vPvB

Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

Section 3: Composition/information on ingredients**3.1 Mixtures****Description**

Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 80-62-6 EINECS: 201-297-1 Reg No. 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit.2, H315; Skin Sens.1, H317; STOT SE 3, H335	>2.5-<10%
CAS: 103-11-7 EINECS: 203-080-7 Reg No. 01-2119453158-37	2- ethylhexyl acrylate Skin Irrit.2, H315; Skin Sens.1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥10-<25%

Additional information

For the wording of the listed risk phrases refer to section 16.

Section 4: First aid measures**4.1 Description of first aid measures****General information**

Immediately remove any clothing soiled by the product.
Take affected persons out of danger area and lay down.
Involve doctor immediately.

After inhalation

In case of unconsciousness place patient stably in side position for transportation. Take affected persons into fresh air and keep them quiet.
Seek medical treatment.

After skin contact

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Skin sensitization
Irritant to skin, eyes and respiratory system

4.3 Indication of any immediate medical attention and special treatment needed

After inhalation, even in the absence of signs of disease, give inhaled Corticoid (e.g. Ventolair).

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, sand, extinguishing powder, foam

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO) Nitrogen oxides (NO_x)

Vapours are heavier than air. Creeping vapours can result in inflammation at a distance.

5.3 Advice for firefighters:

Protective equipment

Wear fully protective suit.

Wear self-contained respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation



Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment.

Keep unprotected persons away.

6.2 Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in the case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7: Handling and storage

7.1 Precautions for safe handling

Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat buildup (pressure increase). Avoid heat.

Do not refill residue back into storage receptacles.

Ensure good interior ventilation in the workplace (fumes are heavier than air), at least 7-fold air changes per hour.

Prevent formation of aerosols.

Information about fire - and explosion protection

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Only explosion-proof equipment.

Protect against electrostatic charges.

Protect from heat.

7.2 Conditions for safe storage, including any incompatibilities:

Storage

Requirements to be met by storerooms and receptacles

Store only in the original receptacle. Store in a cool location.

Information about storage in one common storage facility

Store away from oxidising agents. Store away from foodstuffs.

Further information about storage conditions

Store in cool, dry conditions in well sealed receptacles.

Storage in a collecting room is required.

Store under lock and key and with access restricted to technical experts or their assistants only.

Max storage temperature 30°C.

Keep container tightly sealed.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

Building coating or sealing.

Section 8: Exposure controls/personal protection

Additional information about design of technical facilities No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
80-62-6- methyl methacrylate (≥ 2.5 -<10%)		
WEL		Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
DNELs		
80-62-6 methyl methacrylate		
Inhalative	DNEL (worker)	210 mg/m ³ (Long-term - local effects) 210 mg/m ³ (Long-term – systemic effects) Long-term
	DNEL (population)	74.3 mg/m ³ (Long-term - systemic effects) 105 mg/m ³ (Long-term - local effects)
103-11-7 2-ethylhexyl acrylate		
Dermal	DNEL	242 µg/cm ² (Employee / Industrial / Commercial) Long term and short term
Inhalative	DNEL	37.5 mg/m ³ (Employee / Industrial / Commercial)
PNECs		
80-62-6 methyl methacrylate		
PNEC sediment		1.47 mg/kg dw (ground) 5.74 mg/kg dw (freshwater)
PNEC		0.094 mg/l (seawater) 0.94 mg/l (freshwater)
103-11-72 ethylhexyl acrylate		
Ground		2.3 mg/l (Soil microorganisms) 1 mg/l (ground)
PNEC Water		0.0023 mg/kg (oral intake) 0.126 mg/l (sediment) 0.002727 mg/l (freshwater)

Additional information about design of technical facilities

The lists valid during the making were used as a basis.

8.2. Exposure controls

Protective equipment



General protective and hygienic measures

Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

Respiratory protection

Ensure good ventilation.
In case of brief exposure or low pollution use respiratory filter A1 device. In case of intensive or longer exposure use self-contained A2 respiratory protective device. The use of breath protective hoods can be recommended since no carrying time limits are valid.

Protection of hands

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Select glove material on consideration of the penetration times, rates of diffusion and degradation.
Preventive skin protection by use of skin-protecting agents is recommended. After use of gloves apply skin-cleaning agents and skin cosmetics.
Check protective gloves prior to each use for their proper condition.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Protective gloves according to EN 374.

Suitable material: nitrile.

Penetration time of glove material

Our recommendation is mainly for a one-time use as a short-term protection for liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time must be found out from the manufacturer of the protective gloves and must be observed.

For permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable

Butyl rubber, BR

For permanent contact, gloves made of the following materials are suitable

Butyl rubber, BR

Not suitable are gloves made of the following material

Leather

Eye protection

Tightly sealed goggles, EN-Standard: EN 166

Body protection

Protective work clothing

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information:

Appearance

Form:	Fluid
Colour:	Various colours
Odour:	Ester-like
Odour threshold:	Not determined
pH-value:	Not determined

Change in condition

Melting / Freezing point:	Not determined
Initial boiling point / range:	101 °C (MMA)
Flash point:	23 °C (DIN EN ISO 3680)
Flammable (solid, gas):	N/A
Ignition temperature:	252 °C (2-EHA)
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product is not explosive. However, formation of explosive air / vapour mixtures are possible.

Explosion limits

Lower:	1.7 Vol % (MMA) Not determined
Upper:	12.5 Vol % (MMA) Not determined

Vapour pressure at 20 °C:	0.2 hPa (2-EHA)
Density at 20 °C:	1.8 g/cm ³ (EN ISO 2811-1)
Evaporation rate:	Not determined
Solubility in / Miscibility with water:	Not miscible or difficult to mix
Partition coefficient (n-octanol/water):	log Pow: 4.29 (2-EHA); (25 °C, OECD 107) log Pow: 1.38 (MMA)

Viscosity

Dynamic at 20 °C:	4300 mPas (EN ISO 2555)
--------------------------	-------------------------

Solvent content

Organic solvents	0.1%
VOC (EC):	0.11%
Solids content:	79.1%

9.2 Other information

No further relevant information available.

Section 10: Stability and reactivity

10.1	Reactivity	See Section 10.2
10.2	Chemical stability	
	Thermal decomposition / conditions to be avoided	No decomposition if used according to specifications.
10.3	Possibility of hazardous reactions	Exothermic reaction. Reacts with peroxides and other radical forming substances. A hazardous polymerization may occur after the exhaustion of the inhibitor.
10.4	Conditions to avoid	Heat and direct sunlight.
10.5	Incompatible materials	Reactions with peroxides and other free-radical generators.
10.6	Hazardous decomposition products	No dangerous decomposition when product used according to specifications.
	Additional information	Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan at the workplace where the product is present.

Section 11: Toxicological information

11.1	Information on toxicological effects	There were no toxicological findings to the mixture.
	Acute toxicity	Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4h	>259 mg/l (rat)
------------	---------	-----------------

80-62-6 methyl methacrylate

Oral	LD50 NOAEL	>5000 mg/kg (rat) (OECD 401) 2000 ppm (rat) n drinking water, 6-2000 ppm Findings: no toxic effects
Dermal	LC50	>5000 mg/kg (rabbit)
Inhalative	NOAEL	25 ppm (rat) 24 – 400 ppm Findings: damage to mucous membranes in the nose at 400 ppm
	LC50/4h	29.8 mg/l (rat)

103-11-7 2-ethylhexyl acrylate

Oral	LD50	4435 mg/kg (rat) (BASF Test)
Dermal	LC50	7520 mg/kg (hare)

Primary irritant effect:

Skin corrosion/irritation Causes skin irritation and irritability.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization May cause an allergic skin reaction.

**Other information
(about experimental toxicology)**

Due to the high vapour pressure a harmful concentration in the air is quickly reached. At high concentrations a narcotic effect can occur.

Subacute to chronic toxicity

Not tested.

**Toxiokinetics, metabolism
and distribution**

The drug is metabolized rapidly (MMA)

Repeated dose toxicity

No data available.

**CMR effects (carcinogenicity,
mutagenicity and toxicity
for reproduction)**

Not tested

Germ cell mutagenicity

Based from Germ Cell to Aspiration Hazard.

Carcinogenicity

Based from Germ Cell to Aspiration Hazard.

Reproductive toxicity

Based from Germ Cell to Aspiration Hazard.

STOT-single exposure

Based from Germ Cell to Aspiration Hazard.

STOT-repeated exposure

Based from Germ Cell to Aspiration Hazard.

Aspiration hazard

Based from Germ Cell to Aspiration Hazard.

Section 12: Ecological information**12.1 Toxicity**

80-62-6 methyl methacrylate	
EC3/16h	100 mg/l (Pseudomonas putida) (Cell proliferation inhibition test, Bringmann-Kuehn)
Aquatic toxicity 80-62-6 methyl methacrylate	
EC50/48h LC50/96h ErC50/72h NOEC/72h EC50/72h NOEC	69 mg/l (daphnia magna) (OECD 202) >79 mg/l (Rainbow trout) (OECD 203) >110 mg/l (Pseudokirchneriella subcapitata) (OECD 201) >110 mg/l (Selenastrum capricornutum) (OECD 201) >110 mg/l (Selenastrum capricornutum) (OECD 201) 9.4 mg/l (Danio rerio) (OECD 210) Fish early life stage test, 35 days 37 mg/l (daphnia magna) (OECD 211) 21 days
103-11-7 2-ethylhexyl acrylate	
Other (28d) EC50/48h (static) LC50/96h (static) NOEC/21d	>1000 mg/kg (Soil microorganisms) (OECD 217) The product has not been tested. The statement has been derived from products of a similar structure or composition. 1.3 mg/l (daphnia magna) (OECD 202, Part 1) 1.81 mg/l (Rainbow trout) (OECD 203) 0.19 mg/l (daphnia magna) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/72h (static)	1.71 mg/l (scenedesmus subspicatus) (OECD 201) The details of the toxic effect relates to the analytically determined concentration

12.2 Persistence and degradability	No further information available.
Other information	The product is easily biodegradable.
12.3 Bioaccumulative potential	2-EHA: can be accumulated in organisms; bioaccumulation potential: Bioconcentration Factor 282.4 (Calculated).
12.4 Mobility in soil	MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. 2-EHA The product floats on water and does not dissolve. Absorption in soil is not likely.
Additional ecological information:	
COD-value: 2-EHA	Theoretical oxygen demand (TOD) = 5.6 g / g
BOD5-value	0.14 g/g (MMA)
General notes	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.
12.5 Results of PBT and vPvB assessment	
PBT	Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
vPvB	Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).
12.6 Other adverse effects	No further relevant information available.

Section 13: Disposal considerations

13.1 Waste treatment methods

Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.

Recommendation

Uncured product residues are special waste.
Cured product residues are not hazardous waste.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste disposal key

The following Waste Codes of the European Waste Catalogue (EWC), are considered a recommendation. The disposal must be coordinated with the local waste disposal company.

Liquid product:

080111 * paint and varnish containing organic solvents or other dangerous substances

080199 waste nec

Cured product residues:

080112 paint and varnish wastes other than those mentioned in 080111


080410 adhesive waste adhesives and sealants other than those mentioned in 080409

European waste catalogue 080111 * (recommended)

Uncleaned packaging**Recommendation**

This material and its container must be disposed of as hazardous waste. Disposal must be made according to official regulations.

Section 14: Transport information

14.1	UN-Number	
	ADR, ADN, IMDG	Void
	IATA	UN1263
14.2	UN proper shipping name	
	ADR, ADN, IMDG	Void
	IATA	PAINT
14.3	Transport hazard class(es)	
	ADR, ADN, IMDG	
	Class	Void
	IATA	
		
	Class	3 Flammable liquids
	Label	3
14.4	Packing group	
	ADR, IMDG	Void
	IATA	III
14.5	Environmental hazards:	
	Marine pollutant	No
14.6	Special precautions for user	N/A
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code	N/A
	Transport / Additional information:	
	ADR	
	Remarks	>450 l:3 F1, III (2.2.3.1.5)
	IMDG	
	Remarks	>450 l:3, III (2.3.2.5)
	UN "Model Regulation"	Void

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I

None of the ingredients is listed.

Seveso category

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements

5000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction

3

National regulations:

Information about limitation of use

Employment restrictions under the Maternity Protection Directive (94/33/EC).

Employment restrictions for Maternity Directive (92/85/EEC) for expectant and nursing mothers.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

Section 16: Other information

These figures relate to the product as delivered.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
H412	Harmful to aquatic life with long lasting effects

Training hints

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555). Training about hazards and precautions must take place before the start of employment and at least annually thereafter.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skins Sens 1: Skin sensitization – Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment – long-term aquatic hazard – Category 3

Sources:

www.gestis.de
www.echa.eu
logkow.cisti.nrc.ca

Data compared to the previous version altered.

The information provided in this document is accurate to the best of our knowledge. The document does not constitute a specification and Axter takes no responsibility for the suitability of the product in a particular use. It is the user's responsibility to ensure that the product is suitable for the intended application and use and to take the necessary precautions to ensure that during handling, storage and installation of the product, all regulations to guarantee safety of people and the environment are observed. For further information or technical design assistance, contact Axter Ltd.