

Technical Data Sheet

BUTYL CORD Accessories

1. Presentation	Butyl Cord is a synthetic rubber extruded cord with talc coating to eliminate adhesion during storage and use.
2. Usage	Component within the Exceljoint and Excelpark movement/expansion joint system.
3. Packaging	Cord diameter: 3cm Cord length: 5m Cord weight: 5kg Packed in boxes of 2 cords, weight of box: 11kg
4. Storage	This product should be stored away from heat in a cool, dry place and in its original packaging. Shelf life (sealed in original packaging): 1 year
5. Observations	Installation temperature: $+5^{\circ}\text{C} \leq T \leq +40^{\circ}\text{C}$. Service temperature: $-20^{\circ}\text{C} \leq T \leq +80^{\circ}\text{C}$. No water absorption.

6. Safety

This product should not be used if the temperature of the substrate is lower than 5°C. Safety precautions to be taken when using this product are given in the Material Safety Data Sheet for Hyrastik Evo..

Characteristics	Method	Units	Values	Tolerance
Density		kg/m ³	1120	±10
Viscosity at 20°C	SL 002A	mPa.s	7000	±1500

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.