

Technical Data Sheet

DILUCOAT

1. Description	Xylene-based solvent for use with Starcoat QC liquid applied waterproofing system.
2. Use	<ul style="list-style-type: none">• Diluting Starcoat QC for use with airless application at a rate of 5% to 10% by weight of the product used.• Cleaning installed product.
3. Application Method	Dilution: <ul style="list-style-type: none">• Mix the Dilucoat directly into the drum of the product to be applied or in a can adapted for the purpose.• Mix the component with a slow-speed drill fitted with a suitable paddle to release any air bubbles.• Apply the diluted product normally.
4. Packaging	4kg drum.
5. Storage	Shelf life – 12 months in unopened cans. Store away from heat at a temperature between 5°C and 35°C hermetically sealed in the original packaging.
6. Note	Safety measures to take during application of this product are given in the Dilucoat Safety Data Sheet (SDS).

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.