

Technical Data Sheet

STARCOAT PMMA DECORATIVE CHIPS

Starcoat PMMA Decorative Chips are specifically designed to be used as a topping with Starcoat PMMA liquid waterproofing products. In addition to providing design options for the finished surface, they also enhance the non-slip properties of the waterproofing.

Material

Acrylate-based topping.

Properties and advantages

Can be used as a single colour or multiple colours for a compatible resin product.

Use

Starcoat PMMA Decorative Chips are applied to the Starcoat PMMA sealing layer to enhance the appearance of the finish as well as to optimize the non-slip properties of the surface.

A non-slip level of up to R10 can be achieved.

Packaging

1kg tub and 20kg box.

Colours

Black, white, grey.

Coverage

Up to 50g/m² depending on desired appearance.

Application

Equipment / tools: Hopper gun.

User the hopper spray gun to apply Starcoat PMMA Decorative Chips to the sealer (finish) while the coating is still wet. Depending on the required design of the surface, the coloured chips can first be fixed and a greater or lesser amount applied. However, applying an excess quantity should be avoided, as in their final position the chips applied should not form a continuous coating at any point.

General information

The above information, especially on product application, is based on extensive development work, experience and is provided to the best of our knowledge. However, the wide variety of requirements and conditions on site mean that it is necessary for the product to be tested to ensure that it is suitable for the intended purpose. Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology or improvements to our products. Axter Ltd makes no warranties, express or implied, as to the properties and performance under any variations from such conditions in actual construction.

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.