

Technical Data Sheet

STARCOAT PMMA FLEECE

Starcoat PMMA Fleece is specially designed for use with Starcoat PMMA liquid applied waterproofing systems in terms of material properties, thickness and degree of density. The fleece enables the layer thickness to be controlled when applying the liquid products. It also has a strengthening effect and bridges cracks in the hardened waterproofing layer.

Properties and advantages

- Aids easy and reliable application of waterproofing with layer thickness control function.
- High tear strength and tear propagation resistance.
- High elongation at break.

Material

Mechanically strengthened and heat set special synthetic fibre fleece with a weight per unit area of 110g/m².

Use

Starcoat PMMA Fleece is used as reinforcement and to ensure a minimum layer thickness for Starcoat PMMA liquids, achieving a high quality, flexible waterproofing system.

Packaging

Roll Width X Roll Length	
10.50cm	50m
15.00cm	50m
20.00cm	50m
26.00cm	50m
35.00cm	50m
52.00cm	50m
70.00cm	50m
105.00cm	50m

Colour

White.

Storage

Starcoat PMMA Fleece should be stored in a dry place, in a horizontal position and protected from moisture and dirt.

Product application

A single layer of the Starcoat PMMA Fleece is fully saturated with Starcoat PMMA liquid waterproofing when applied. There must be an overlap of at least 5cm at joints. For further information refer to the Product Data Sheet (PDS) for the Starcoat PMMA liquid waterproofing products or contact Axter Ltd.

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.