

Technical Data Sheet

Thermecran

1. Description	Thermecran is a high strength, glass-fibre reinforced modified bitumen perforated membrane with a polyester film under surface.
2. Use	<ul style="list-style-type: none"> Partially bonded base layer in torch-on, single or multi-layer waterproofing systems such as Hyranger TS. Perforated vapour diffusion layer under a torch-applied air vapour control layer (AVCL).
3. Packaging	20m ² rolls (20m x 1m) with a nominal weight of 25kg.
4. Storage	Rolls to be stored upright, without stacking and under cover. 30 rolls per pallet.
5. Composition	(Indicative).

Thickness	1mm
Surface finish	Sanded
Under surface	Thermofusible film

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.