

Technical Data Sheet

VERNIS SEAL Primer

Presentation	Modified, synthetic, resin-based product with pigment in organic solvent.
Use	Primer used to improve the bonding of waterproofing membranes on to concrete, metal and timber decks.
Packaging	25 L container.
Storage	Containers should be kept upright. The product can be stored for up to 24 months from the date of manufacture in its original packaging, uncovered and in cool, ventilated conditions.
Instructions for use	Coverage: 100 to 150g/m ² . Drying time: 1 to 2 hours. Substrates: apply Vernis Seal to substrates that are dry and clean with no loose particles. Metal areas should be rust- and grease-free. Application: apply Vernis Seal with a brush, roller or spray gun. Do not apply too liberally, the colour in the primer allows easy identification of the areas that have been primed.
Safety	Inflammable product, use in the open air or in a well ventilated area. Use in accordance with health and safety precautions for solvents and refer to the Material Data Safety Sheet (MSDS). Tools should be cleaned with Cetoline thinner or MEK.

CHARACTERISTICS	
Density	0.92
Viscosity CF n°4 to 23°C	10s
Dry extract NFT 30013 to 105°C	15.7%
Flash point	- 4°C

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.