

Technical Data Sheet

WATER FLOW REDUCING LAYER SEALANT STRIP

1. Description	Water Flow Reducing Layer Sealant Strip (WFRLSS) is an A-grade butyl strip sealant used in conjunction with Axter's Water Flow Reducing Layer.
2. Application method	For airsealing and weatherproofing the following: <ul style="list-style-type: none">• Lap joints within sheeting and cladding systems.• Lap joints of metal decking beneath flat roof systems.• For joint sealing control layers.
3. Key features	<ul style="list-style-type: none">• High airsealing and weatherproofing performance.• Extremely flexible and strong.• High tack.• Standard colour - grey/black and white available to special order.• Application temperature +5°C to +40°C.• Service temperature range -40°C to +110°C.

Suitable for use with a variety of substrates:**Recommended:**

- Steel.
- Aluminium.
- GRP / PVC.
- Uncoated Glass.
- Timber (painted or stained).

Compatible:

- Fibre cement.
- Gutter joints.



CODE	THICKNESS X WIDTH (MM)	ROLL LENGTH (M)	ROLLS PER CARTON
A - 1 x 12 x 45	1 x 12	45	20
A - 1.5 x 9 x 30	1.5 x 9	30	24
A - 2 x 12 x 22.5	2 x 12	22.5	20
A - 3 x 9 x 15 + 12	3 x 9	15	12
A - 3 x 9 x 15 + 24	3 x 9	15	24
A - 3 x 19 x 15	3 x 19	15	14
A - 3 x 50 x 15	3 x 50	15	6
A - 6 x 50 x 5	6 x 50	5	6
A - 4 x 18 x 12	4 x 18	12	14
A - 5 x 6 x 9.6 + 15	5 x 6	9.6	15
A - 5 x 6 x 9.6 + 30	5 x 6	9.6	30
A - 4 dia x 12	4 diameter	12	30
A - 6 dia x 8	6 diameter	8	24
A - 8 dia x 6	8 diameter	6	20
A - 10 dia x 5	10 diameter	5	20

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.