

# Technical Data Sheet

## WILOTEKT SURFACE CONDITIONING PRIMER Wilotekt®-Plus Structural Waterproofing System

|                              |  |
|------------------------------|--|
| <b>1. Description</b>        | <p>Wilotekt Surface Conditioner is a black, liquid, solvent-based, toluene free, fast drying bitumen primer with adhesive and is supplied ready to use, as part of the Wilotekt-Plus structural waterproofing system.</p>  |
| <b>2. Use</b>                | <p>Bitumen-based primer used on all substrates (concrete, screeds, metal and timber) before the installation of the Wilotekt-Plus structural waterproofing to provide a good key for the system and to protect the substrate from moisture.</p>  |
| <b>3. Application method</b> | <p>Brush, roller or spray apply the Wilotekt Surface Conditioner to the prepared, clean and dry structure and allow to dry completely before continuing the application of the remaining Wilotekt-Plus waterproofing components.<br/>Drying time: 60-90 mins.<br/>Cleaning tools: petroleum solvents.</p> <p>Installation details of the Wilotekt-Plus system are shown in the Axter Wilotekt-Plus Brochure available from: <a href="http://www.axter.co.uk/downloads">www.axter.co.uk/downloads</a></p> <p>The Wilotekt-Plus system must be installed by Axter accredited installers who have completed upskilling in this system. More information is available here: <a href="http://axter.co.uk/installer-membership">axter.co.uk/installer-membership</a></p> |
| <b>4. Product details</b>    | <p>Unit weight:<br/>25 l /drum<br/>22 drums/pallet<br/>Average consumption:<br/>150-300g/m<sup>2</sup></p>   |
| <b>5. Packaging</b>          | <p>Wilotekt Surface Conditioner is supplied in 25L drums.</p>  |

|                                |   |
|--------------------------------|---|
| <b>6. Handling</b>             | Anyone handling this product should be aware of suitable working techniques, gestures and postures.<br>Operatives should use appropriate personal protective equipment - refer to Section 8 of the Safety Data Sheet -SDS-Axter Wilotekt Surface Conditioner V10 0119.  |
| <b>7. Storage</b>              | The drums must be stored in a well ventilated area, away from naked flames and electrostatic charge.<br>Shelf life (sealed in unopened, original packing):<br>2 years from date of manufacture.<br>kept dry.  |
| <b>8. Disposal / Re-use</b>    | <b>Disposal</b> Proper waste management of the mixture and/or its container must be carried out in accordance with current regulations. Refer to Safety Data Sheet: SDS-Axter Wilotekt Surface Conditioner V10 0119, Section 13.<br><b>Re-use</b> When installed as part of a complete hot melt waterproofing system, the product becomes an integral part of the structure that cannot be removed for processing and is disposed of at the end of life of the structure. |
| <b>9. Additional documents</b> | Axter Wilotekt-Plus Brochure  |
| <b>10. Certification</b>       | BBA Certificate 22-6518<br>ETA 03-0049<br>ISO 9001-2015 Certificate No. 1996/5190.13<br>ISO 14001-2015 Certificate No. 2011/40665.5   |
| <b>11. Safety Data Sheet</b>   | SDS - Axter Wilotekt Surface Conditioner V10 0119<br>The above documents are available at <a href="http://www.axter.co.uk/downloads">www.axter.co.uk/downloads</a>  |

| CHARACTERISTICS              |            |
|------------------------------|------------|
| Density                      | 0.94+-0.05 |
| Solid content                | 54% +-2%   |
| Viscosity at 25°C (CF no. 4) | 16 - 30s   |
| Flash point                  | 26°C       |

NA=not applicable due to use of product.

NPD=no performance determined.

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at [www.axter.co.uk/downloads](http://www.axter.co.uk/downloads). Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: [technical@axterltd.co.uk](mailto:technical@axterltd.co.uk), telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.