

Technical Data Sheet

WILOTEKT REINFORCEMENT MESH

Wilotekt®-Plus Structural Waterproofing System

1.	Description	Wilotekt glass-fibre reinforcement mesh is the reinforcement element and forms an integral part of the Wilotekt®-Plus structural waterproofing system.
2.	Use	Wilotekt reinforcement mesh is used as the first layer to form the reinforcement of the system and to control the flow of the hot-applied Wilotekt compound.
3.	Application method	<p>The Wilotekt Reinforcement Mesh is loose laid on to the horizontal surfaces of the primed structure and rolled out with minimum 80mm overlaps.</p> <p>Installation details of the Wilotekt-Plus system are shown in the Axter Wilotekt-Plus Brochure available from: axter.co.uk/downloads.</p> <p>The Wilotekt-Plus system must be installed by Axter accredited installers who have completed an upskilling course in this system. More information on the Axter accredited installer schemes is available here: axter.co.uk/installer-membership.</p>
4.	Product details	<p>Roll size: 100m x 1m roll</p> <p>Colour: Purple</p> <p>Mesh size: 6 x 6.5mm</p> <p>Nominal roll weight: 15kg/roll</p> <p>15 rolls/pallet</p>
5.	Product characteristics	<p>Tensile strength: Unit: N/50mm; Value: ≥ 1100</p> <p>Tensile elongation: Unit: %; Value: $\geq 3.1\%$</p>
6.	Packaging	Supplied in shrink wrapped rolls on a pallet, packaging to be removed before use.

7. Handling	Anyone handling this product should be aware of suitable working techniques, gestures and postures. Operatives should use appropriate personal protective equipment, including wearing protective gloves.
8. Storage	The rolls must be kept dry. Do not expose to naked flame. Shelf life (in sealed packaging): 1 year.
9. Disposal / Re-use	<p>Disposal This product is non hazardous. Any roll waste will be minimal and should be disposed of in accordance with local regulations. Used waste and packaging should be processed according to local regulations.</p> <p>Re-use When installed as part of a complete hot melt waterproofing system, the product becomes an integral part of the structure that cannot be removed for processing and is disposed of at the end of life of the structure.</p>
10. Additional documents	Axter Wilotekt-Plus Brochure
11. Certification	BBA Certificate 22-6518 ETA 03-0049 ISO 9001-2015 ISO 14001-2015
12. Safety Data Sheet	SDS - Axter Wilotekt Reinforcement Mesh V1 1120
The above documents are available at: www.axter.co.uk/downloads	

NA: not applicable due to use of product.

NPD: no performance determined.

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk, telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.