

Technical Data Sheet

WILOTEKT REINFORCEMENT MESH Wilotekt®-Plus Structural Waterproofing System

1. Introduction	Wilotekt glass-fibre reinforcement mesh is the reinforcement element and forms an integral part of the Wilotekt®-Plus structural waterproofing system.
2. Use	Wilotekt reinforcement mesh is used as the first layer to form the reinforcement of the system and to control the flow of the hot-applied Wilotekt compound.
3. Presentation	Wilotekt reinforcement mesh is packaged in 100m x 1m rolls. Colour: purple. Mesh size: 6 x 6.5mm. Roll weight: 105-115 g/m ²
4. Tensile strength Tensile elongation	Unit: N/50mm; Value: ≥ 1100 Unit: %; Value: $\geq 3.1\%$
5. Storage	Wilotekt reinforcement mesh is supplied in shrink wrapped rolls. The rolls must be kept dry. Do not expose to naked flame. Shelf life (unsealed packaging): 1 year.
6. Comments	Dispose of all surplus materials in appropriate designated containers. Non-hazardous waste.

NA: not applicable due to use of product. NPD: no performance determined.

Wilotekt®-Plus Accreditation: BBA Certificate 22-6518; European Technical Assessment ETA 03/0049.

Axter reserves the right to modify and update this data at any time without prior notice. Characteristics provided in this publication derive from data obtained under controlled test conditions. Axter makes no warranties, express or implied, as to the properties and performance under any variations from such conditions in actual construction.

It is the user's responsibility to verify with Axter Ltd the intended implementation of the product and that the current version of this document is being used, to ensure suitability and compliance with specifications and project requirements, industry regulations, legislation and good practice, installation techniques and other relevant guidance. Axter technical documents are available at www.axter.co.uk/downloads.

Contact Axter Ltd for further assistance.