

Technical Data Sheet

WILOTEKT SURFACE CONDITIONER Wilotekt®-Plus Structural Waterproofing System

1. Introduction	Wilotekt Surface Conditioner is a black, liquid, solvent-based, fast drying, bitumen primer modified with adhesive and supplied ready to use.
2. Use	Bitumen-based primer used on all substrates (concrete, screeds, metal and timber) before the installation of Wilotekt®-Plus structural waterproofing to provide a good key for the system and to protect the substrate from moisture.
3. Presentation	Wilotekt Surface Conditioner is packaged in 25l drums. Average consumption: 150-300 g/m ² .
4. Storage	Wilotekt Surface Conditioning Primer must be stored in a well ventilated area. The product must be kept away from naked flames and electrostatic charge. Shelf life (sealed in unopened, original packaging): 2 years from date of manufacture.
5. Composition	Solvent phase bitumen, fast drying aromatic solvents; toluene free.
6. Application	By brush or roller on dry, clean surface. Allow to dry completely before applying waterproofing membrane. Drying time: 60-90 mins. Cleaning tools: petroleum solvents.

CHARACTERISTICS	
Density	0.94+-0.05
Solid content	54% +-2%
Viscosity at 25°C (CF no. 4)	16 - 30s
Flash point	26°C

Wilotekt®-Plus Accreditation: BBA Certificate 22-6518; European Technical Assessment ETA 03/0049.

NA: not applicable due to use of product.

NPD: no performance determined.

Axter reserves the right to modify and update this data at any time without prior notice. Characteristics provided in this publication derive from data obtained under controlled test conditions. Axter makes no warranties, express or implied, as to the properties and performance under any variations from such conditions in actual construction.

It is the user's responsibility to verify with Axter Ltd the intended implementation of the product and that the current version of this document is being used, to ensure suitability and compliance with specifications and project requirements, industry regulations, legislation and good practice, installation techniques and other relevant guidance. Axter technical documents are available at www.axter.co.uk/downloads.

Safety precautions to comply with when using this product are given in the Wilotekt Surface Conditioner Safety Data Sheet. It is essential not to eat, drink or smoke while using this product. It is harmful by inhalation, skin contact and ingestion. Do not dispose of product into drains.

Contact Axter Ltd for further assistance.