

# Technical Data Sheet

## VERNIS SEAL Primer

|                             |   |
|-----------------------------|---|
| <b>Presentation</b>         | Modified, synthetic, resin-based product with pigment in organic solvent.   |
| <b>Use</b>                  | Primer used to improve the bonding of waterproofing membranes on to concrete, metal and timber decks.   |
| <b>Packaging</b>            | 25kg container.   |
| <b>Storage</b>              | Containers should be kept upright.<br>The product can be stored for up to 24 months from the date of manufacture in its original packaging, uncovered and in cool, ventilated conditions.   |
| <b>Instructions for use</b> | Coverage: 100 to 150 g/m <sup>2</sup> .<br>Drying time: 1 to 2 hours.<br>Substrates: apply Vernis Seal to substrates that are dry and clean with no loose particles. Metal areas should be rust- and grease-free. Application: apply Vernis Seal with a brush, roller or spray gun. Do not apply too liberally, the colour in the primer allows easy identification of the areas that have been primed. |
| <b>Safety</b>               | Inflammable product, use in the open air or in a well ventilated area.<br>Use in accordance with health and safety precautions for solvents and refer to the Material Safety Data Sheet.<br>Tools should be cleaned with Cetoline thinner or MEK.   |

| CHARACTERISTICS                |                     |
|--------------------------------|---------------------|
| Density                        | 0.92 ± 0.05 to 20°C |
| Viscosity CF n°4 to 23°C       | 10s                 |
| Dry extract NFT 30013 to 105°C | 15.7% ± 3%          |
| Flash point                    | - 4°C               |

The manufacturer reserves the right to modify, at any time, the characteristics of this product.