

Safety Data Sheet

According to Regulation (EC) No. 1907/2006

VERNIS SEAL

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: VERNIS SEAL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Professional use only

Bonding primer on concrete substrate

1.3. Details of the supplier of the safety data sheet

Supplier

AXTER LTD, West Road, Ransomes Europark, Ipswich IP3 9SX UK

Tel: +44 (0) 1473 724056, 8.00 am to 5.30 pm, Monday to Friday

Email: info@axterltd.co.uk

1.4 Emergency telephone

+ 44 1473 724056 (NOT 24HRS - 8am - 5.30pm, Monday Friday)

In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

Section 2: Hazards identification

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Repeated exposure may cause skin dryness or cracking (EUH066).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS07



GHS02

Signal Word:
DANGER

Product identifiers:
607-022-00-5

ETHYL ACETATE

Hazard statements:
H225
H319
H336
EUH066

Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

Precautionary statements - Prevention:
P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical equipment.

P242

Use only non-sparking tools.

P261

Avoid breathing vapours.

P264

Wash hands thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:
P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
Call a Poison Centre or doctor/physician if you feel unwell.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use dry powder for extinction.

P312

P337 + P313

P370 + P378

Precautionary statements - Disposal:

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

Precautionary statements - Disposal:

P501

Dispose of contents/container to an approved center as a hazardous material

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with Annex XIII of the REACH regulations EC 1907/2006.

Section 3: Composition/information on ingredients

3.2. Mixtures Composition:

Identification	(EC) 1272/2008	Note	%
INDEX: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46 ETHYL ACETATE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	[1]	$50 \leq x \% < 100$
CAS: 28553-12-0 EC: 249-079-5 REACH: 01-2119430798-28 DIISONONYL PHTHALATE:		[1]	$2.5 \leq x \% < 10$

(Full text of H-phrases: see section 16).

Information on ingredients:

[1] Substance for which maximum workplace exposure limits are available.

Section 4: First aid measures

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation:

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.
If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.
If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
Watch out for any remaining product between skin and clothing, watches, shoes, etc.
If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital. DO NOT use solvents or diluents

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Keep the person exposed at rest. Do not force vomiting.
Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary.
Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

Section 5: Firefighting measures

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:

- water with AFFF (Aqueous Film Forming Foam) additive
- foam
- multipurpose ABC powder

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet
- water

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO²)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.
Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of collected waste in compliance with current regulations.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures.

Do not discard rinsing agents down the drain.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

Refer to section 13 for waste disposal rules.

Section 7: Handling and storage

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air. Prevent the formation of flammable or explosive concentrations in air and avoid vapour concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected. Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapours.

Avoid inhaling vapours. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapour extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions. In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging:

Vats

Drums

Suitable packaging materials:

Metal

Unsuitable packaging materials:

Plastic

7.3. Specific end use(s)

No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits:

ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS	TWA	STEL	Ceiling	Definition	Criteria
141-78-6	400 ppm	-	-	-	-

Germany - AGW (BAuA - TRGS 900, 29/01/2018):

CAS	VME	VME	Excess	Notes
141-78-6	-	200ppm 730mg/m ³	-	2(l)

France (INRS - ED984:2016):

CAS	VME-ppm	VME-mg/m ³	VLE-ppm	VLE-mg/m ³	Notes	TMP No
141-78-6	400	1400	-	-	-	84

European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 98/24/CE):

CAS	VME-ppm	VME-mg/m ³	VLE-ppm	VLE-mg/m ³	Notes
141-78-6	200	734	400	1468	-

UK / WEL (Workplace exposure limits, EH40/2005, 2011):

CAS	TWA	STEL	Ceiling	Definition	Criteria
141-78-6	200 ppm -mg/m ³	400 ppm -mg/m ³	-	-	-
28553-12-0	- ppm 5 mg/m ³	- ppm - mg/m ³	-	-	-

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ETHYL ACETATE (CAS: 141-78-6)

Final use:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Final use:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Exposure method:

Potential health effects:

DNEL:

Workers.

Dermal contact.

Long term systemic effects.

63 mg/kg body weight/day

Inhalation.

Short term local effects.

1468 mg of substance/m³

Inhalation.

Long term systemic effects.

734 mg of substance/m³

Inhalation.

Long term local effects.

734 mg of substance/m³

Inhalation.

Short term systemic effects.

1468 mg of substance/m³

Consumers.

Ingestion.

Long term systemic effects.

4.5 mg/kg body weight/day

Dermal contact.

Long term systemic effects.

37 mg/kg body weight/day

Inhalation.

Short term local effects.

734 mg of substance/m³

Inhalation.

Long term systemic effects.

367 mg of substance/m³

Inhalation.

Long term local effects.

367 mg of substance/m³

Inhalation.

Short term systemic effects.

734 mg of substance/m³

Predicted no effect concentration (PNEC):

DIISONONYL PHTHALATE (CAS: 28553-12-0)

Environmental compartment: Soil.

PNEC: 30 mg/kg

ETHYL ACETATE (CAS: 141-78-6)

Environmental compartment: Soil.

PNEC: 0.22 mg/kg

Environmental compartment: Fresh water.

PNEC: 0.26 mg/l

Environmental compartment: Sea water.

PNEC: 0.026 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 1.65 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 0.34 mg/kg

Environmental compartment: Marine sediment.

PNEC: 0.034 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 650 mg/l

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides
accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses
during work where they may be exposed to irritant vapours.**Hand protection**Use suitable protective gloves that are resistant to chemical agents
in accordance with standard EN374. Gloves must be selected
according to the application and duration of use at the workstation.
Protective gloves need to be selected according to their suitability
for the workstation in question: other chemical products that may
be handled, necessary physical protections (cutting, pricking, heat
protection), level of dexterity required.

Body protection

Type of gloves recommended:
Butyl Rubber (Isobutylene-isoprene copolymer)
Recommended properties:
Impervious gloves in accordance with standard EN374
Avoid skin contact.
Wear suitable protective clothing.
Work clothing worn by personnel shall be laundered regularly.
After contact with the product, all parts of the body that have been soiled must be washed.

Respiratory protection

Avoid breathing vapours.
If the ventilation is insufficient, wear appropriate breathing apparatus.
When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.
Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:
A2 (Brown)

Section 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****General information:**

Physical state: Viscous liquid.

Important health, safety and environmental information

pH: Not relevant.
Boiling point/boiling range: > 35°C
Flash Point: -4.00 °C.
Vapour pressure (50°C): Below 110 kPa (1.10 bar).
Density: 0,92 g/cm³ (a 20°C)
Water solubility: Insoluble.
Viscosity: 10 seconds (Coupe Ford N°4)
Melting point/melting range: Not specified.
Self-ignition temperature: Not specified.
Decomposition point/decomposition range: Not specified.

9.2. Other information

VoC (g/l): 773

Section 10: Stability and reactivity**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.)

Avoid:

must not be allowed on the premises.
Accumulation of electrostatic charges.
Heat
Flames and hot surfaces

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition
may release/form:

carbon monoxide (Co)
carbon dioxide (Co₂)

Section 11: Toxicological information**11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

No toxicological data available for the substances.

Acute toxicity:

DIISONONYL PHTHALATE (CAS: 28553-12-0)

oral route: LD50 > 10000 mg/kg

Species: Rat

Dermal route: LD50 > 3160 mg/kg

Species: Rabbit

Inhalation route: LC50 > 4.4 mg/l

Species: Rat

Germ cell mutagenicity:

DIISONONYL PHTHALATE (CAS: 28553-12-0)

No mutagenic effect.

Carcinogenicity:

DIISONONYL PHTHALATE (CAS: 28553-12-0)

Carcinogenicity Test: Negative.

No carcinogenic effect.

Species: Rat

Reproductive toxicant:

DIISONONYL PHTHALATE (CAS: 28553-12-0)

No toxic effect for reproduction

11.1.2. Mixture

No toxicological data available for the mixture.

Section 12: Ecological information

12.1. Toxicity

12.1.1. Substances

DIISONONYL PHTHALATE (CAS: 28553-12-0)

Fish toxicity:	LC50 > 102 mg/l Species: Brachydanio rerio Duration of exposure: 96 h other guideline Species: oryzias latipes
Crustacean toxicity:	EC50 > 74 mg/l Species: Daphnia magna Duration of exposure: 48 h Other guideline
Aquatic plant toxicity:	ECr50 > 88 mg/l Species: Others Duration of exposure: 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.2.1. Substances

DIISONONYL PHTHALATE (CAS: 28553-12-0)

Biodegradability:	Rapidly degradable. DBO5/DCO = 0.81
-------------------	----------------------------------------

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

Section 13: Disposal considerations

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Do not eliminate with household waste.

Do not discard rinsing agents down the drain.

Soiled packaging:

Empty container completely. Keep label(s) on container.
Give to a certified disposal contractor.

Local arrangements:

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances
15 01 10 * packaging containing residues of or contaminated by dangerous substances

Section 14: Transport information

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

14.1. UN number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

Classification:



3

14.4. Packing group

II

14.5. Environmental hazards

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	5 L	163 367 640D 650	E2	2	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	II	5 L	F-E,S-E	163 367	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	II	353	5 L	364	60 L	A3 A72 A192	E2
	3	-	II	Y341	1 L	-	-	A3 A72 A192	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG. For excepted quantities,

see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **Classification and labelling information included in section 2:**

The following regulations have been used:

Regulation EC 1272/2008 modified by regulation EC 618/2012

EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

15.2. Chemical safety assessment

No data available.

Section 16: Other information

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations:

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

ADR: European agreement concerning the international carriage of dangerous goods by Road.

MDG: International Maritime Dangerous Goods.

IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefährdungsklasse (Water Hazard Class).

GHS02: Flame

GHS07: Exclamation mark